Effect of seaweed addition on enhanced anaerobic digestion of food waste and sewage sludge

Sang-Ryong Shin, Mo-Kwon Lee, Seongwon Im, Dong-Hoon Kim[†]

Department of Civil Engineering, Inha University, Incheon 22212, Republic of Korea

ABSTRACT

To investigate the effect of seaweed (SW) addition on anaerobic co-digestion of food waste (FW) and sewage sludge (SS), batch experiments were conducted at various substrate concentrations (2.5, 5.0, 7.5, and 10.0 g volatile solids (VS)/L) and mixing ratios ((FW or SS):SW = 100:0, 75:25, 50:50, 25:75, and 0:100 on a VS basis). The effect of SW addition on FW digestion was negligible at low substrate concentration, while it was substantial at high substrate concentrations by balancing the rate of acidogenesis and methanogenesis. At 10 g VS/L, CH₄ production yield was increased from 103 to 350 mL CH₄/g VS by SW addition (FW:SW = 75:25). On the other hand, SW addition to SS enhanced the digestion performance at all substrate concentrations, by providing easily biodegradable organics, which promoted the hydrolysis of SS. *k_{hyd}* (hydrolysis constant) value was increased from 0.19 to 0.28 d⁻¹ by SW addition. The calculation showed that the synergistic CH₄ production increment by co-digesting with SW accounted for up to 24% and 20% of total amount of CH₄ production in digesting FW and SS, respectively.

Keywords: Co-digestion, Food waste, Seaweed, Sewage sludge, Synergistic effect

1. Introduction

Due to the high content of organic matters and moisture, organic solid wastes such as food waste (FW) and sewage sludge (SS) generate huge amount of odor, leachate, and greenhouse gases during their decomposition. Thus, they should be handled through appropriate treatment methods including anaerobic digestion (AD), which was proven as an environmentally friendly technology capable of recovering bioenergy in the form of methane (CH₄) [1-3]. AD is a biological process, consisting of four steps of reaction: hydrolysis, acidogenesis, acetogenesis, and methanogenesis, and the balance among each step is known to be critical for the successful digestion performance [4].

The characteristics of FW might vary depending on the region and season, but it is generally characterized to have a high C/N ratio (20 to 50) and salinity concentration (2 to 5%), and insufficient trace element for the stable long-term operation [5, 6]. Also, FW contains a huge amount of easily biodegradable carbohydrates, causing the excessive hydrolysis and acidogenesis [7]. It could result in the accumulation of organic acids with pH drop under high-strength condition [8]. To avoid this failure, anaerobic digesters fed with FW should be operated at a low organic loading

rate (OLR) range, from 1 to 4 g volatile solids (VS)/L/d, or long hydraulic retention time (HRT) up to 80 d [9, 10]. On the other hand, SS has a poor hydrolysis rate due to having microbial cells and extracellular polymers substances (EPS). The EPS are composed of various substances such as protein, carbohydrates, lipids, nucleic acids, and humic acids [11]. It forms a tight extracellular matrix to prevent the penetration of hydrolytic enzymes during AD [12]. To overcome this barrier, physical, thermal, and biological pretreatment methods have often been applied to SS, but their economic benefit is still questioned [13].

Extensive researches have been carried out on co-digestion, which can overcome some problems in the mono-digestion such as lack of trace elements, imbalanced C/N ratio, and high or low biodegradability [14-16]. For example, Zhang et al. [14] reported a 40% increase in a total CH₄ production yield (MPY) compared to the mono-digestion of FW, by co-digesting with cattle manure at a FW/cattle manure ratio (on a VS basis) of 2. They mentioned the supply of buffer capacity and lowering C/N ratio, as the main cause of the increased performance. Higher amount of CH₄ was produced by adding microalgae to SS, which was ascribed to the fact that the easily biodegradable portion in microalgae helped the degradation of SS [17].

This is an Open Access article distributed under the terms of the Creative Commons Attribution Non-Commercial License (<http://creativecommons.org/licenses/by-nc/3.0/>) which permits unrestricted non-commercial use, distribution, and reproduction in any medium, provided the original work is properly cited.

Copyright © 2019 Korean Society of Environmental Engineers

Received August 6, 2018 Accepted November 2, 2018

[†] Corresponding author

Email: dhkim77@inha.ac.kr

Tel: +82-32-860-7562 Fax: +82-32-873-7560

ORCID: 0000-0002-0471-9982

Since 2000, the third-generation biomass has gained a lot of attention as a bioenergy feedstock, owing to its negligible lignin content, and higher CO₂ uptake rate than terrestrial biomass. In particular, seaweed (SW) does not require land for its growth, and is easier to cultivate compared to the fresh-water algae. SW, for example brown algae, is, in general, composed of 30 to 40% carbohydrates, 35 to 40% of minerals, 15% of proteins, and 5% of lipids. It has a higher content of carbohydrates than SS, and its main carbohydrate unit is cellulose while it is starch in case of FW [18, 19]. Starch and cellulose are well known polysaccharides consisting glucose units, while their binding patterns are different with each other. In starch, each glucose is bound with α -linked connection, while each glucose is bound to β -linked connection in cellulose [20]. This structural feature can lead to the big differences in the biodegradability because β -linked is stronger than α -linked.

In the present work, we hypothesized that SW has a lower anaerobic biodegradability than FW, while higher biodegradability than SS, which in turn, a certain amount of SW addition to these organic solid wastes might enhance AD performance. To investigate this, batch anaerobic co-digestion experiments were performed at various substrate concentrations (2.5, 5.0, 7.5, 10.0 g VS/L) and mixing ratios ((FW or SS):SW = 100:0, 75:25, 50:50, 25:75, 0:100 on a VS basis). The synergistic increment by co-digestion with SW was calculated, and the reasons were revealed by monitoring pH and organic acids during digestion, and by applying first-order kinetic model.

2. Materials and Methods

2.1. Seeding Inoculum and Feedstock

The granular sludge taken from the anaerobic digester in a wastewater treatment plant of local beer factory in Cheongju, South Korea, was used as an inoculum after grinding less than 2 mm of diameter. Prior to seeding, it was kept at 35°C for two weeks to remove residual biogas. FW was collected from the cafeteria in Inha University, where around 1,000 people eat two times of meal every day. It was also ground with blender having less than 2 mm of diameter. *Laminaria japonica*, which collected at Yeosu of South Korea, was chosen as a SW, and it was washed with tap water to remove salt, and dried at 105°C for 2 h. Then,

the dried SW was pulverized with blender, and diluted with distilled water. The SS used in this study was the mixture of primary sludge and secondary sludge at the same volume ratio, taken from the local wastewater treatment plant. The characteristics of seeding inoculum and feedstock are shown in Table 1.

2.2. Experiment

The co-digestion experiments were conducted by using 280 mL serum bottle, with a working volume of 100 mL. The seeding inoculum was injected into each serum bottle at a concentration of 7.5 g VS/L. Substrate concentrations of co-substrates (1. FW and SW, and 2. SS and SW) were set to 2.5, 5.0, 7.5, and 10.0 g VS/L at the mixing ratios of 100:0, 75:25, 50:50, 25:75, and 0:100 on a VS basis. The corresponding I/S (inoculum to substrate on a VS basis) ratios were 3.0, 1.5, 1.0, and 0.8 at each substrate concentration of 2.5, 5.0, 7.5, and 10.0 g VS/L, respectively. In addition, an experiment was conducted to produce CH₄ from the inoculum itself, and all results presented exclude this CH₄ production. The initial pH was adjusted between 7.8 and 8.0 with 2 N KOH solution, and then sufficiently replaced with nitrogen gas (99.999%) to provide anaerobic condition. Nutrients media including buffer were not added to clarify the role of SW in the co-digestion. The fermentation was carried out in an incubator (VS-8480SRN, VISION Co., Korea) set at 35°C and at the agitation speed of 150 rpm. All experiments were conducted duplicates, and the results were averaged. Gas and liquid samples were taken every 2-5 d to analyze biogas amount, CH₄ content, pH, and organic acids.

2.3. Analysis

The concentration of total solids (TS), VS, total nitrogen (TN), alkalinity (as g CaCO₃/L), and total chemical oxygen demand (COD) were measured according to standard methods [21], while carbohydrate concentration was determined by the colorimetric method [22]. pH value was measured using a pH meter (HM-3R, DDK-TOA). The amount of biogas produced was measured using a gas syringe, and was converted to standard temperature and pressure (STP). CH₄ gas content was measured by taking 0.5 mL of the gas phase in serum bottle with Gas-tight syringe (HAMILTON CO., USA) and using gas chromatography (GOWMAC series 580, USA) equipped with a thermal conductivity detector. The temperature of injector, column, and detector was set to 50, 80, and 70°C,

Table 1. Characteristics of Seeding Sludge, Food Waste, Sewage Sludge, and Seaweed

Item	Units	Seeding sludge	Food waste	Sewage sludge	Seaweed
TS ^a	g/L	31.3	83.6	24.2	26.3
VS ^a	g/L	27.4	77.2	18.9	20.7
COD ^a	g/L	37.8	104.6	29.9	26.9
Alkalinity	g CaCO ₃ /L	4.1	N.D. ^a	1.1	N.D. ^a
Carbohydrate	g COD/L	-	62.2	2.0	12.5
TN ^a	g/L	-	2.9	2.3	0.6
C/N ratio ^a	-	-	36.0	13.0	44.8

^aTS = Total solids; VS = Volatile solids; COD = Chemical oxygen demand; N.D. = Not detectable; TN = Total nitrogen; C/N ratio = COD/TN ratio

respectively. The column was a 183 cm (Length) 0.32 cm (Diameter) stainless steel column with porapak Q (80/100 mesh). Nitrogen (N_2 , 99.999%) gas was used as the carrier gas and the flow rate maintained at 30 mL/min. The organic acids were analyzed by HPLC (Model VP, Shimadzu Co., Japan) after filtered the supernatant in the reactor with a 0.2 μ m membrane.

2.4. Synergistic Effect

In this study, the amount of CH_4 production at mono-digestion of each substrate was used to determine the increased CH_4 production at co-digestion. The amount of CH_4 production increase by the synergistic effect was calculated by defining as follows (Eq. (1)):

$$\text{Synergistic } CH_4 = M_a - ((A \times C_1) + (B \times C_2)) \quad (1)$$

where ' M_a ' was the actual amount of CH_4 production, while ' A ' and ' B ', were the amount of CH_4 production from the mono-digestion of FW or SS, and SW, respectively. ' C_1 ' and ' C_2 ' indicates the mixing ratios in co-digestion of FW or SS and SW, respectively. In other words, the value of ' $((A \times C_1) + (B \times C_2))$ ' indicates the expected amount of CH_4 production in the co-digestion of FW or SS with SW.

2.5. Kinetic Model Applied

First-order kinetic model has been widely applied in AD of organic matter, in particular, SS degradation [23, 24]. The amount of cumulative CH_4 production in the anaerobic co-digestion of SS and SW was fitted using the first-order kinetic model as shown below (Eq. (2)):

$$M_{(t)} = F_d \times (1 - e^{-k_{hyd}t}) \quad (2)$$

where ' $M_{(t)}$ ' is the cumulative CH_4 production at time (mL CH_4); ' F_d ' is maximum CH_4 production potential (mL CH_4); ' k_{hyd} ' is hydrolysis rate constant (d^{-1}); and ' t ' is digestion time (d).

3. Results and Discussion

3.1. Comparison of Biodegradability

The biodegradability under anaerobic condition of individual feedstock can be determined at a low substrate concentration (2.5 g VS/L), under which both substrate and product inhibition on AD are negligible [25]. CH_4 production began as soon as the digestion started, indicating that the seeding inoculum was suitable for degrading all types of feedstock (Fig. 1). The MPY increased up to 10 d, and reached 425, 344, and 169 mL CH_4 /g VS in cases of FW, SW, and SS, respectively. These amounts correspond to the CH_4 conversion efficiency (MCE) (actual CH_4 production/theoretical CH_4 production, on a COD basis of 1 g COD = 350 mL CH_4) of 89, 76, and 31%, respectively. This difference in the AD performance might be linked to the characteristics of main composition of individual feedstock. SS has less biodegradability than other feedstocks, since it is mainly composed of diverse

Fig. 1. Cumulative CH_4 production yield in the anaerobic digestion of food waste (FW), sewage sludge (SS), and seaweed (SW) at 2.5 g VS/L.

microorganisms and organic and inorganic compounds clumped together in a polymeric network by EPS [13], while FW and SW have a high content of carbohydrates that are easier to degrade. However, the main carbohydrates in FW consist of starch, whereas the carbohydrates of SW (brown algae) are mostly composed of cellulose [18, 19, 26]. As previously mentioned, each glucose is bound to the next glucose by either 1,4- α or 1,6- α glycosidic bonds (α -linked) in starch, while each glucose is bound to the next glucose by 1,4- β glycosidic bonds (β -linked) in cellulose [20]. The fact that β -linked is stronger than α -linked is why AD performance of SW was less than FW. As hypothesized, the biodegradability of SW was found to be between FW and SS, which could be a suitable co-digesting material for enhanced AD.

3.2. Co-digestion of FW and SW

3.2.1. Performance and synergistic effect

The amount of CH_4 production, MPY, and MCE are arranged in Table 2. Biogas production was completed within 14 d, and hydrogen production was negligible during whole experimental period (Fig. S1). The MPY of FW (FW:SW = 100:0) decreased as substrate concentration increased. In particular, there was a huge drop at 10 g VS/L, exhibiting only 103 mL CH_4 /g VS. In cases of low substrate concentration range (2.5, 5.0 g VS/L) in FW digestion, SW addition did not show any improvement. It rather decreased the MPY, probably due to the less biodegradable characteristics of SW compared to FW. However, in cases of high substrate concentration range (7.5 and 10.0 g VS/L) of FW digestion, the MPY significantly increased, by up to 1.2 and 3.5 times at 7.5 and 10.0 g VS/L, respectively. In terms of MCE, SW addition increased MCE from 60% to 74% and 22% to 76% at 7.5 and 10.0 g VS/L, respectively. By applying Eq. (1), it was found that the ' $\text{Synergistic } CH_4$ ' was negligible at low concentration, while it was increased at high concentration with SW addition increase. In particular, 85 mL CH_4 /g VS of ' $\text{Synergistic } CH_4$ ' was produced at a substrate concentration of 10.0 g VS/L and FW:SW = 25:75, accounting for the 24% of total amount of CH_4 produced. To

Table 2. Batch Performances in the Anaerobic Co-digestion of Food Waste (FW) and Seaweed (SW) at various substrate Concentrations and Mixing Ratios

	2.5 [*] (100:0) ^a	2.5 (75:25)	2.5 (50:50)	2.5 (25:75)	2.5 (0:100)	5.0 (100:0)	5.0 (75:25)	5.0 (50:50)	5.0 (25:75)	5.0 (0:100)	7.5 (100:0)	7.5 (75:25)	7.5 (50:50)	7.5 (25:75)	7.5 (0:100)	10.0 (100:0)	10.0 (75:25)	10.0 (50:50)	10.0 (25:75)	10.0 (0:100)
Actual CH ₄ production (mL)	106	101	97	93	86	198	187	177	167	160	212	226	240	255	245	103	168	265	350	319
CH ₄ production yield (mL CH ₄ /g VS)	422	402	390	373	344	395	375	353	334	320	282	300	319	340	327	103	168	265	350	319
CH ₄ conversion efficiency ^b (%)	89	76	84	81	76	83	80	76	73	71	60	64	69	74	72	22	36	57	76	70
Expected CH ₄ production ^c (mL)		100	95	91		189	179	170				220	228	237			157	211	265	
Synergistic CH ₄ ^d (mL)		1	2	2		-2	-2	-3				6	12	18			11	55	85	

^{*}Substrate concentration unit = g VS/L

^aMixing ratios = (FW:SW) on a VS basis

^bActual CH₄ production/theoretical CH₄ production (COD basis, 1 g COD = 350 mL CH₄)

^cIt was obtained by “((A × C₁) + (B × C₂))”, where ‘A’ and ‘B’ are the amount of CH₄ production from mono-digestion of FW and SW, while ‘C₁’ and ‘C₂’ are the mixing ratios in co-digestion of FW and SW, respectively.

^dActual CH₄ production – Expected CH₄ production

explain the reasons for the synergistic effect, some analytical results are shown in the next chapter.

3.2.2. Reasons of synergistic effect

The change of pH during digestion and cumulative organic acids concentration are shown in Fig. 2 and Table 3, respectively. When FW was digested alone at 2.5 g VS/L, the cumulative organic acids concentration was negligible, and the pH remained high near 7.0. The SW addition showed little effect on the change

of pH and organic acids accumulation at 2.5 g VS/L. On the other hand, in the mono-digestion of FW at 10.0 g VS/L, organic acids were accumulated to over 7,000 mg COD/L, and pH rapidly dropped to about 5.5, which did not recover above 6.5 until the end of digestion. This indicates that the drop of AD performance at high substrate concentrations of FW was due to the excessive production of organic acids, while the rate of methanogenesis process could not follow at high substrate concentration. Organic wastes, which contain many readily biodegradable organic matters

Fig. 2. The variation of pH in anaerobic co-digestion of food waste (FW) and seaweed (SW) at (a) 2.5 g VS/L, and (b) 10.0 g VS/L.**Table 3.** Cumulative Organic Acids Concentration in the Broth in Co-digestion of Food Waste (FW) and Seaweed (SW) at 2.5 and 10.0 g VS/L (Samples were taken after 12 d and 14 d of operation.)

	2.5 [*] (100:0) ^a	2.5 (75:25)	2.5 (50:50)	2.5 (25:75)	2.5 (0:100)	10.0 (100:0)	10.0 (75:25)	10.0 (50:50)	10.0 (25:75)	10.0 (0:100)
Organic acids (mg COD/L)	40	20	50	70	60	7,430	6,530	2,330	1,020	320

^{*}Substrate concentration unit = g VS/L

^aMixing ratios = (FW:SW) on a VS basis

such as FW, cause process failure due to quick hydrolysis [27, 28]. However, in case of SW mono-digestion, there seemed to be a balance between the rate of acidogenesis and methanogenesis even at 10 g VS/L. Compared to FW digestion, the cumulative organic acids concentration was lower, and pH drop was less. As mentioned earlier, this might ascribe to the difference in the biodegradable characteristics between FW and SW that they have similar anaerobic biodegradability (in terms of MCE or MPY), but different rate. In addition, although alkalinity concentration of raw SW was negligible, there might have been a production of buffering materials from SW like microalgae. In a previous work of Yun et al. [29], there was an increased concentration of alkalinity during anaerobic acidogenesis of microalgae, which was attributed to the release of buffering materials caused by cell hydrolysis. Therefore, it can be concluded that SW addition to FW under high organic loading is beneficial to gain high CH_4 production with maintaining high MPY and MCE. However, other factors such as supplementing of trace elements like Ni, Co, Fe, and Se rich in SW [5, 30], and the dilution of salinity might also have contributed to the enhanced digestion performance [6, 31]. These effects can be critical in the continuous operation, but chances are low in the batch-type operation. The seeding inoculum (digester sludge) generally contains enough amounts of trace elements, which would be depleted in the long-term operation [32].

3.3. Co-digestion of SS and SW

3.3.1. Performance and synergistic effect

In co-digestion of SS and SW, biogas production was completed within 8 and 14 d, and hydrogen production was negligible during whole experimental period (Fig. S2). Compared to FW and SW, the MPY of SS was lower, ranging 170–180 mL $\text{CH}_4/\text{g VS}$ (Table 4). However, the inhibition at high substrate concentration was negligible, probably indicating that initial steps (hydrolysis or acidogenesis) rather than the final step (methanogenesis) in AD were

the rate-limiting step in using SS as a feedstock. Under all substrate concentrations, SW addition to SS substantially increased the digestion performance. For example, MPY and MCE at 10.0 g VS/L increased from 180 to 308 mL $\text{CH}_4/\text{g VS}$, and from 33 to 64%, respectively. However, it could not be a surprising result since SW had a higher biodegradability than SS as seen in Fig. 1.

Therefore, it is very important to see the synergistic effect in co-digestion of SS by employing Eq. (1). It was found that the ‘Synergistic CH_4 ’ increased with SW addition increase at all substrate concentrations. In particular, 51 mL of ‘Synergistic CH_4 ’ was produced at 10.0 g VS/L and SS:SW = 75:25, accounting for the 20% of the total amount of CH_4 produced. Assuming that MPY of SW was equal in all cases, this meant that SW addition triggered the anaerobic biodegradation of SS. To explain the reasons for the synergistic effect, some analytical results are shown in the next chapter.

3.3.2. Reasons of synergistic effect

The amount of cumulative CH_4 production in the anaerobic co-digestion of SS and SW was well fitted ($R^2 > 0.98$) using first-order kinetic model (Eq. (2)). As shown in Table 5, F_d and k_{hyd} increased with SW addition increase, at both low (2.5 g VS/L) and high concentration (10.0 g VS/L). In particular, k_{hyd} is an important indicator reflecting hydrolysis rate and substrate biodegradability [23, 24]. k_{hyd} value in the co-digestion of SS and SW at 10.0 g VS/L and the mixing ratio of SS:SW = 75:25 was increased about 37% (0.19 to 0.26) compared to AD of SS alone (10.0 g VS/L, SS:SW = 100:0). In addition, as shown in Fig. 3, further and faster pH drop with SW addition confirmed the promoting effect on the hydrolysis and acidogenesis of SS [10]. However, when SW was digested alone, it showed lower k_{hyd} value compared to the mixed cases, probably due to the too much pH drop below 6.5. Like our study, many studies have been reported to increase the AD efficiency by improving the hydrolysis rate of SS through co-digestion of substrates with higher biodegradability than SS.

Table 4. Performances in the Anaerobic Co-digestion of Sewage Sludge (SS) and Seaweed (SW) at Various Substrate Concentrations and Mixing Ratios

	2.5*	2.5	2.5	2.5	2.5	5.0	5.0	5.0	5.0	5.0	7.5	7.5	7.5	7.5	7.5	10.0	10.0	10.0	10.0	10.0
	(100:0) ^a	(75:25)	(50:50)	(25:75)	(0:100)	(100:0)	(75:25)	(50:50)	(25:75)	(0:100)	(100:0)	(75:25)	(50:50)	(25:75)	(0:100)	(100:0)	(75:25)	(50:50)	(25:75)	(0:100)
Actual CH_4 production (mL)	42	55	70	78	86	87	108	130	154	160	133	169	199	233	245	180	267	278	308	319
CH_4 production yield (mL $\text{CH}_4/\text{g VS}$)	170	220	276	310	344	174	215	261	309	320	177	224	265	310	326	180	267	278	308	319
CH_4 conversion efficiency ^b (%)	31	42	55	65	76	31	41	52	64	71	32	42	52	65	72	33	50	55	64	70
Expected CH_4 production ^c (mL)	-	53	64	75	-	-	105	124	142	-	-	161	189	217	-	-	216	251	285	-
Synergistic CH_4 ^d (mL)	-	2	5	2	-	-	3	6	12	-	-	7	10	16	-	-	51	26	23	-

*Substrate concentration unit = g VS/L

^aMixing ratios = (SS:SW) on a VS basis

^bActual CH_4 production/theoretical CH_4 production (COD basis, 1 g COD = 350 mL CH_4)

^cIt was obtained by “ $((A \times C_1) + (B \times C_2))$ ”, where ‘A’ and ‘B’ are the amount of CH_4 production from mono-digestion of FW and SW, while ‘C₁’ and ‘C₂’ are the mixing ratios in co-digestion of FW and SW, respectively.

^dActual CH_4 production – Expected CH_4 production

Table 5. Estimated Parameters Obtained through the First-order Kinetic Model

	2.5 ^a (100:0) ^b	2.5 (75:25)	2.5 (50:50)	2.5 (25:75)	2.5 (0:100)	10.0 (100:0)	10.0 (75:25)	10.0 (50:50)	10.0 (25:75)	10.0 (0:100)
R ²	0.98	0.99	0.99	0.98	0.99	0.98	0.99	0.98	0.99	0.99
F _d ^c	57	66	77	86	92	218	296	302	340	363
k _{hyd} ^c	0.40	0.44	0.46	0.50	0.51	0.19	0.26	0.28	0.27	0.24

^aSubstrate concentration unit = g VS/L^bMixing ratios = (sewage sludge:seaweed) on a VS basis^cF_d and k_{hyd} were the values obtained through the first-order kinetic equation of $M(t) = F_d \times ((1 - e^{-k_{hyd}t}))$, where 'M(t)' is the actual CH₄ production at time (mL CH₄); 'F_d' is maximum CH₄ production potential (mL CH₄); 'k_{hyd}' is hydrolysis rate constant (d⁻¹); and 't' is digestion time (d). **Fig. 3.** The variation of pH in anaerobic co-digestion of sewage sludge (SS) and seaweed (SW) at (a) 2.5 g VS/L, and (b) 10.0 g VS/L.

For example, Zhang et al. [33] reported the increase of MPY to 82% in the co-digestion at SS:pig manure = 1:2, with k_{hyd} value increase from 0.062 to 0.094. Zhen et al. [34] also found that the addition of aquatic plant (*Egeria densa*) increased the MPY by 19% and k_{hyd} value from 0.175 to 0.194 as compared to digestion of SS alone. To reveal the reason of increased CH₄ production by FW addition on SS digestion, Yun et al. [35] observed the increased activity of protease when FW was added. Therefore, it can be concluded that SW addition could provide easily biodegradable organics to anaerobic consortium, which promoted the hydrolysis of SS, and accordingly, enhanced the AD performance.

4. Conclusions

The anaerobic biodegradability of SW was found to be between FW and SS, which acted as a suitable co-digesting material for enhanced AD of FW and SS. At low substrate concentration of FW digestion, SW addition showed a negligible effect on AD performance, while it synergistically enhanced the performance by balancing acidogenesis and methanogenesis at high substrate concentrations. At 10 g VS/L and FW:SW = 25:75, MCE increased from 22 to 76% by SW addition. On the other hand, SW addition to SS synergistically enhanced the digestion performance at all

substrate concentrations, by providing easily biodegradable organics to anaerobic consortium, which promoted the hydrolysis of SS.

Acknowledgments

This work is supported by the “R&D Center for Reduction of Non-CO₂ Greenhouse gases” (2017002410003) funded by Korea Ministry of Environment (MOE) as “Global Top Environment R&D Program”.

References

- Li K, Liu R, Sun C. Comparison of anaerobic digestion characteristics and kinetics of four livestock manures with different substrate concentrations. *Bioresour. Technol.* 2015;198:133-140.
- Xie T, Xie S, Sivakumar M, Nghiem LD. Relationship between the synergistic/antagonistic effect of anaerobic co-digestion and organic loading. *Int. Biodeterior. Biodegrad.* 2017;124: 155-161.
- Zhao J, Liu Y, Wang D, et al. Potential impact of salinity on methane production from food waste anaerobic digestion. *Waste Manage.* 2017a;67:308-314.

4. Feng Q, Lin Y. Integrated processes of anaerobic digestion and pyrolysis for higher bioenergy recovery from lignocellulosic biomass: A brief review. *Renew. Sust. Energ. Rev.* 2017;77: 1272-1287.
5. Zhang L, Jahng D. Long-term anaerobic digestion of food waste stabilized by trace elements. *Waste Manage.* 2012;32:1509-1515.
6. Zhao J, Liu Y, Wang D, et al. Potential impact of salinity on methane production from food waste anaerobic digestion. *Waste Manage.* 2017b;67:308-314.
7. Kumar G, Sivagurunathan P, Park JH, Kim SH. Anaerobic digestion of food waste to methane at various organic loading rates (OLRs) and hydraulic retention times (HRTs): Thermophilic vs. mesophilic regimes. *Environ. Eng. Res.* 2016;21:69-73.
8. Wang P, Wang HT, Qiu YQ, Ren LH, Jiang B. Microbial characteristics in anaerobic digestion process of food waste for methane production – A review. *Bioresour. Technol.* 2017b;248: 29-36.
9. Cecchi F, Traverso P, Pavan P, Bolzonella D, Innocenti L. Characteristics of the OFMSW and behavior of the anaerobic digestion process. In: Mata-Alvarez J, ed. Biomethanization of the organic fraction of municipal solid waste. UK: IWA; 2003. p. 141-180.
10. Banks CJ, Chesshire M, Heaven S, Arnold R. Anaerobic digestion of source-segregated domestic food waste: Performance assessment by mass and energy balance. *Bioresour. Technol.* 2011;102:612-620.
11. Yang Q, Luo K, Li XM, et al. Enhanced efficiency of biological excess sludge hydrolysis under anaerobic digestion by additional enzymes. *Bioresour. Technol.* 2010;101:2924-2930.
12. Sun J, Guo L, Li Q, et al. Structural and functional properties of organic matters in extracellular polymeric substances (EPS) and dissolved organic matters (DOM) after heat pretreatment with waste sludge. *Bioresour. Technol.* 2010;219:614-623.
13. Dhar BR, Nakhla G, Ray MB. Techno-economic evaluation of ultrasound and thermal pretreatments for enhanced anaerobic digestion of municipal waste activated sludge. *Waste Manage.* 2010;32:542-549.
14. Zhang C, Xiao G, Peng L, Su H, Tan T. The anaerobic co-digestion of food waste and cattle manure. *Bioresour. Technol.* 2013;129:170-176.
15. Grosser A, Neczaj E, Singh BR, Almås ÅR, Brattebø H, Kacprzak M. Anaerobic digestion of sewage sludge with grease trap sludge and municipal solid waste as co-substrates. *Environ. Res.* 2017;155:249-260.
16. Shin JD, Han SS, Eom KC, Sung SW, Park SW, Kim HO. Predicting methane production potential of anaerobic co-digestion of swine manure and food waste. *Environ. Eng. Res.* 2008;13:93-97.
17. Olsson J, Feng XM, Ascue J, et al. Co-digestion of cultivated microalgae and sewage sludge from municipal waste water treatment. *Bioresour. Technol.* 2014;171:203-210.
18. Ohkouchi Y, Inoue Y. Direct production of L(+)-lactic acid from starch and food wastes using *Lactobacillus manihotivivans* LMG18011. *Bioresour. Technol.* 2006;97:1554-1562.
19. Chen J, Bai J, Li H, Chang C, Fang S. Prospects for bioethanol production from macroalgae. *Trend. Renew. Energ.* 2015a;1: 185-197.
20. Johnson AW. Invitation to organic chemistry. Massachusetts: Jones & Bartlett Learning; 1998.
21. APHA. Standard methods for the examination of water and wastewater. 22nd ed. Washington D.C.: American Public Health Association; 2012.
22. Dubois M, Gilles KA, Hamilton JK, Rebers PA, Smith F. Colormetric method for determination of sugars and related substances. *Anal. Chem.* 1956;28:350-356.
23. Xie S, Hai FI, Zhan X, et al. Anaerobic co-digestion: A critical review of mathematical modelling for performance optimization. *Bioresour. Technol.* 2016;222:498-512.
24. Lee EY, Cumberbatch J, Wang M, Zhang Q. Kinetic parameter estimation model for anaerobic co-digestion of waste activated sludge and microalgae. *Bioresour. Technol.* 2017;228:9-17.
25. El-Mashad HM, Zhang R. Biogas production from co-digestion of dairy manure and food waste. *Bioresour. Technol.* 2010;101:4021-4048.
26. Chen H, Zhou D, Luo G, Zhang S, Chen J. Macroalgae for biofuels production: Progress and perspectives. *Renew. Sust. Energ. Rev.* 2015b;47:427-437.
27. Haider MR, Zeshan, Yousaf S, Malik RN, Visvanathan C. Effect of mixing ratio of food waste and rice husk co-digestion and substrate to inoculum ratio on biogas production. *Bioresour. Technol.* 2015;190:451-457.
28. Li Q, Li H, Wang G, Wang X. Effects of loading rate and temperature on anaerobic co-digestion of food waste and waste activated sludge in a high frequency feeding system, looking in particular at stability and efficiency. *Bioresour. Technol.* 2017;237:231-239.
29. Yun YM, Jung KW, Kim DH, Oh YK, Shin HS. Microalgal biomass as a feedstock for bio-hydrogen production. *Int. J. Hydrogen Energ.* 2012;37:15533-15539.
30. Karlsson A, Einarsson P, Schnurer A, Sundberg C, Ejlertsson J, Svensson BH. Impact of trace element addition on degradation efficiency of volatile fatty acids, oleic acid and phenyl acetate and on microbial populations in a biogas digester. *J. Biosci. Bioeng.* 2012;114:446-452.
31. Drennan MF, DiStefano TD. High solids co-digestion of food and landscape waste and the potential for ammonia toxicity. *Waste Manage.* 2014;34:1289-1298.
32. Kim DH, Kim SH, Kim HW, Kim MS, Shin HS. Sewage sludge addition to food waste synergistically enhances hydrogen fermentation performance. *Bioresour. Technol.* 2011;102:8501-8506.
33. Zhang W, Wei Q, Wu S, et al. Batch anaerobic co-digestion of pig manure with dewatered sewage sludge under mesophilic conditions. *Appl. Energ.* 2014;128:175-183.
34. Zhen G, Lu X, Kobayashi T, Li YY, Xu K, Zhao Y. Mesophilic anaerobic co-digestion of waste activated sludge and *Egeria densa*: Performance assessment and kinetic analysis. *Appl. Energ.* 2015;148:78-86.
35. Yun YM, Cho SK, Kim HW, Jung KW, Shin HS, Kim DH. Elucidating a synergistic effect of food waste addition on the enhanced anaerobic digestion of waste activated sludge. *Korean J. Chem. Eng.* 2014;31:1542-1546.