Evaluation of physicochemical and heavy metals characteristics in surface water under anthropogenic activities using multivariate statistical methods, Garra River, Ganges Basin, India

MohdYawar Ali Khan^{1,2,3*}, Jie Wen^{2,4}

¹Department of Hydrogeology, King Abdulaziz University, Jeddah 21589, Saudi Arabia

²Department of Hydraulic Engineering, Tsinghua University, Beijing- 100084, China

³Department of Earth Sciences, Indian Institute of Technology Roorkee, Roorkee - 247667, India

⁴China Institute of Water Resources & Hydropower Research (IWHR), Beijing 100044, China

ABSTRACT

Water samples from twenty-six locations were collected during March 2014, to evaluate the spatial variation in the water quality of Garra River, Ganges Basin. The physicochemical and heavy metals concentration along the river water were significantly different between the natural and urbanized areas. In the case of the mainstream, the chemical oxygen demand (COD) and the biological oxygen demand (BOD₅), which indicate the levels of organic pollution of the river water, were in the range of 8.1 - 51.4 mg/L and 5.8 - 26.9 mg/L, respectively. On the other hand, in the case of tributaries, these values were in the range of 19 - 36 mg/L and 11.2 - 20 mg/L, respectively. Multivariate statistical analysis was also carried out to discriminate sources of spatial variation of water quality. The results of principal component analysis (PCA) show the relationship between physicochemical parameters suggesting that the quality of water is mostly controlled by carbonate weathering. Dolomite is most likely to be present, which is a common source of Ca⁺ and Mg⁺. Spatial distribution of PO₄³⁻ with a high concentration in the downstream area of river (average 0.35 mg/L) suggests runoff from agricultural fields in this region as the main source.

Keywords: Garra River, Ganges Basin, Heavy metals, Multivariate statistical analysis, Water quality

1. Introduction

Surface water quality is one of the most critical environmental concerns in many parts of the world. Manahan [1] stated that surface water consists of all the water that flows through landmasses like creeks, springs, lakes, rivers and oceans. A stream is a system involving mainstream rivers and tributaries that transports a one-way flow of large amounts of particulate and dissolved load from both anthropogenic and natural sources. At any point, the chemistry of surface water of a river reflects several noteworthy influences, including atmospheric inputs, the lithology of the basin, anthropogenic inputs and climatic conditions [2]. Natural (erosion) and anthropogenic (agricultural discharge) activities affect the quality of regional surface water [3-10]. According to Finnveden et al. [11], crop waste, degradable solid waste and food waste contribute to the organic content of surface water. Nutrients such

as nitrogen (N) and phosphorus (P) cause the growth of algae and phytoplankton, leading to eutrophication. River water quality research helps to develop water management and pollution prevention strategies. Examining the water quality of the river by considering its organic and physicochemical properties helps to reduce the implication in the clarification of water quality due to spatial variations [12].

Recent research has increasingly focused on planning new monitoring strategies [13, 14], in which multivariate statistical techniques such as PCA and hierarchical cluster analysis (HCA) have emerged. These methods have been used to assess the effectiveness of surface water quality monitoring networks, plans to increase the number of examining stations and select the basic parameters of water quality. Along these lines, it is conceivable to identify and evacuate stations as well as repetitive parameters to reduce the economic cost of monitoring plan without sacrific-

This is an Open Access article distributed under the terms of the Creative Commons Attribution Non-Commercial License (<http://creativecommons.org/licenses/by-nc/3.0/>) which permits unrestricted non-commercial use, distribution, and reproduction in any medium, provided the original work is properly cited.

Copyright © 2021 Korean Society of Environmental Engineers

Received May 27, 2020 Accepted November 18, 2020

* Corresponding author

Email: makhan7@kau.edu.sa

Tel: +966-545274691

ORCID: 0000-0001-6524-4733

ing fluctuation in water quality data. A typical drawback of such techniques is that they can only focus on identifying monitoring locations to be discontinued. This is a consequence of the evaluation being centered on the data of water quality already acquired, ignoring the attributes of the river basin under investigation [13]. Despite this, PCA and HCA have been greatly recognized and widely used in monitoring plans, optimizing spatial sampling points and determining the most appropriate water quality factors [15-24].

The Ganges is an indispensable sacred river in India, especially for the widely practised Hindu religion in the country. In the past few decades, the water quality of the river has deteriorated due to anthropogenic factors, which has led to many national and international organizations to analyze and develop plans to clean the river. In 2009, the National Ganga River Basin Authority (NGRBA) was established under the Environment (Protection) Act of 1986 to clean up the Ganges [25]. The main tributaries are also important contributors to pollution; therefore, conversation strategies should also apply to tributaries.

The tributaries of the Ganges that have been well studied are Gomti, Hindon, Yamuna and Ramganga [26-35]. However, the important tributary in terms of pollution, the Garra River, lacks such an assessment. This river acts as a discharge point for the treated wastewater effluents in adjacent cities. Due to the diversity of the catchment area, anthropogenic and non-anthropogenic pollution sources were discovered along the river.

Therefore, this study investigated the assessment of physicochemical parameters and heavy metals in the water quality of the Garra River and its tributaries and identified the contaminated stretches of the river. This survey was designed to assess the productivity of the Garra River water quality monitoring network using PCA, HCA, Pair sample *t*-test, and one way ANOVA. Subsequently, it is recommended to identify sampling locations that are critical to the monitoring plan; select the most detailed water quality parameters and assess potential sources, either anthropogenic or natural-based, which will affect the water quality of each sampling location. Therefore, there is a need to contribute to changes in the monitoring plan and to guide executives in decision-making and priorities.

2. Study Area

The Garra River originates from the eastern part of the Nainital district of the Kumaon Himalayas, Uttarakhand state (Fig. 1). The total length of the river is 382 km of which the initial 41 km flowing in the Kumaon Himalayas. The river enters in the Ganga Flood Plains (GFP) at Nanakmatta town, where the famous Nanaksagar dam has been built. After the confluence of the Ramganga, another major tributary of the Ganges, the river is connected to the Ganges River in the Kannauj area of Uttar Pradesh [36-39]. The average elevation of the Garra river is 530 m above sea level (a.s.l) with a total catchment area of 6,832 km².

In GFP, river flow through densely populated districts and highly industrial and agricultural areas of Uttar Pradesh state, such as Pilibhit, Shahjahanpur, Hardoi and Kannauj. The river serves as

Fig. 1. Map showing the area of study and sampling locations.

a source of water for domestic and agricultural purpose. The diversity of the river has implications on the pollution sources as both natural and anthropogenic pollution sources are being present. This makes its study interesting and challenging in identifying various sources of pollution.

2.1. Physiography and Relief

Due to The contrast between the landform, slope and elevation, the entire catchment area shows a large variation in weather and climate (Fig. S1). The annual average precipitation in the catchment area is about 1,000 mm, controlled by Indian monsoon (http://www.indiawaterportal.org/met_data/). The altitude of the river ranges from less than 150m a.s.l for GFP to more than 2,000m a.s.l for the Himalayas (Fig. S1(a) and S1(b)). The minimum slope of the river is shown in GFP, which is about 0-1%, and in the Himalayas, it is greater than 15% (Fig. S1(b)). From Fig. S1(d), it is evident that the population density of the catchment area ranges from below 1,000,000 in the Himalayas to more than 3,000,000 in GFP.

2.2. Geology

In the mountain, the catchment constitutes the major lithotectonic

zones, namely Sub-Himalayas consisting of siltstone, clays, sandstones and boulders. It shows the characteristics of the molasse sediments of Mid-Miocene to Pleistocene [40]. In GFP, which is closely linked with the extension of the Himalayan orogenic belt, the basin area represents the quaternary lithostratigraphic sequence, including (1) Varanasi Older Alluvium with two facies i.e. sandy facies and silt clay facies, (2) Ganga/Ramganga Terrace Alluvium and (3) Ganga/Ramganga Recent Alluvium. The latter two constitute the Newer Alluvium [41].

3. Materials and Methods

3.1. Description of the Sampling Sites and Analysis

Fig. 1 shows 26 sampling sites that were consciously identified and observed along the 382 km stretch of the Garra River. Five liters of the river water were collected in the month of March, 2014 from each sampling location. According to the standard protocols [42], all samples have been preserved and transferred to the laboratory. Digital meters (HACH Instruments) were used to measure the pH and electrical conductivity (EC) of each water sample. Total dissolved solids (TDS) and temperature were measured by using an automatic TDS meter (HACH Instruments) and a mercury thermometer (HACH Instruments), respectively. The Winkler Azide method and the molybdate ascorbic acid method were used to determine chemical oxygen demand (COD) and phosphate (PO_4^{3-}), respectively (Spectrophotometer, HACH). On the other hand, the dichromate reflux method was used to determine the biological oxygen demand (BOD_5). Ion chromatographer (IC) (Metrohm 782 Basic IC) was used to determine the concentration of potassium (K^+), magnesium (Mg^{2+}), sodium (Na^+), calcium (Ca^{2+}), lithium (Li^+), chloride (Cl^-), fluoride (F^-), sulfate (SO_4^{2-}), nitrate (NO_3^-) and bicarbonate (HCO_3^-). The ion instrument was calibrated by using a standard solution of cations and anion eluents. The IC detection limit of various cations and anions was 0.1 mg/L.

The concentrations of heavy metals such as iron (Fe), zinc (Zn), and manganese (Mn) were measured by an atomic absorption spectrometer (AAS) (THERMO FISHER. MODEL iCE3000) according to the procedure recommended by Environmental Protection Agency (EPA, Method 3005A). All samples were filtered using a 0.45 μm cellulose nitrate membrane and digested with aquaregia (HNO_3 67%: HCl 37% = 3:1). The samples were covered with ribbed watch glass and heated on a hot plate at 90 to 95° C until the volume was reduced to 15-20 mL. All lamps used in AAS for heavy metal analysis were a hollow cathode. The detection limit were 0.05 mg/L, 0.001 mg/L, 0.01 mg/L for Fe, Zn, and Mn, respectively. To maintain the quality of the data of each processed sample, a blank was carried through the analysis and sample preparation. These blanks may help determine if the sample is contaminated.

3.2. Software Used for Statistical Analysis

Excel 2003, a part of the Microsoft Office Suite, SPSS 10 (IBM Corporation, Windows version) and STATISTICA 6 (StatSoft, Inc.) were used. Statistical analysis such as HCA, paired sample t-test, PCA, and analysis of variance (ANOVA) with a confidence level of $p < 0.05$ were used.

4. Results and Discussion

The examination of the physicochemical and heavy metals characteristics in this study was subjected to statistical analysis and evaluated to their recommended values prescribed in the Bureau of Indian Standard [43] and the World Health Organization [44] (as shown in Table S1).

4.1. Physicochemical Characteristics

Salt solubility, biodegradation, physicochemical parameters and dissolved oxygen rate are exaggerated by temperature [45]; therefore it plays an important role in a riverine system. The temperature of the Garra River and its tributaries range between 24.9°C to 31.8°C with an average of 28.9°C, which is higher than the recommended values by the BIS [43] and WHO [44] (Fig. S2(a)). Generally, the upstream temperature values are lower compared to the middle and downstream. The increase in solar radiation from the morning to noon may be the reason for variation in temperature values (Fig. S2(a)) because the samples were collected at different times between morning and noon.

The pH variation in mainstream water and its tributaries were 6.6 to 8.7 and 7.4 to 8.0 respectively. This confirms that it is slightly alkaline in nature. This is attributable to the HCO_3^- ion concentration, which is relatively high in the tributaries (148.9 mg/L) and the mainstream (151.1 mg/L) (Table S1). Higher pH values of 7.8 (GR2) and 7.6 to 8.7 (GR9-GR20) were recorded in the main river stream, while pH values of 8.1 (T3) and 8.0 (T5) were observed in the tributaries (Fig. S2(b)). Most samples of the Garra River and its tributaries have lower pH values than those set by BIS [43] and WHO [44].

The turbidity in the stream implies the ambiguity of the water due to the presence of suspended matter of clay, silt, waste and other particulate materials. Along the Garra River, the water at the sampling stations GR9 - GR20 was found to be the most turbid, between 178 NTU – 1,355 NTU. GR10 and GR14 exhibited the lowest and highest turbidity values, respectively. In the case of tributaries, the turbidity range is between 111 NTU – 336 NTU, with T1 being the lowest and T6 has the highest turbidity value. Peat water from highlands due to weathering and erosion may be the cause of upstream turbidity. In the middle and downstream of the river, the contribution to turbidity is mainly due to the disturbance of the topsoil by agriculture and other processes such as sand mining, as rivers usually move downwards from hilly areas [46]. Contaminated runoff from industry, agriculture, markets and roads is the main reason for the high turbidity values of these stations (Fig. S2(b)), which are located around urbanized cities such as Pilibhit, Shahjahanpur and Hardoi.

The temperature influences the electrical conductivity (EC) of water, which is an assessment of dissolved solids in water. The average EC values in the water samples from the Garra River and its tributaries (Fig. S2(c)) were 242.6 $\mu\text{S}/\text{cm}$ and 222.5 $\mu\text{S}/\text{cm}$, respectively. As can be seen from Fig. S2(c), in the case of River Garra, the highest EC values are 498 $\mu\text{S}/\text{cm}$ and 421 $\mu\text{S}/\text{cm}$ at GR12 and GR20, respectively, while in the tributaries, the highest values is 340 $\mu\text{S}/\text{cm}$ at T4. Fig. S2(c) shows that the change in EC is almost the same as TDS. In the case of the Garra River

Fig. 2. Spatial variations in COD, BOD₅, and DO in water of Garra River and its tributaries.

and its tributaries, the values of EC shows an increasing pattern from upstream to downstream (Fig. S2(c)). This which may be due to the presence of inorganic dissolved solids such as Cl⁻, NO₃⁻, SO₄²⁻, and PO₄³⁻ (Fig. 3(d) and 3(e)), resulting from industrial effluent discharge and agricultural runoff. The EC value of the entire basin is less than 1,000 μ S/cm, which is the threshold value for water to be described as unpolluted and fresh.

COD and BOD₅ determine the level of organic pollution in lakes and rivers. COD estimates biodegradable and non-biodegradable contamination, while BOD₅ defines the biodegradable fractions. The COD and BOD₅ values in the water collected from the Garra River ranged from 8 mg/L to 51 mg/L and 6 mg/L to 27 mg/L, respectively. However, in the tributaries, these values ranged from 19 mg/L to 36 mg/L and 11 mg/L to 20 mg/L, respectively (Fig. 2(a)). It can be seen from Fig. 2(a) that the COD and BOD₅ values in the middle and downstream of the river increase significantly, which may be due to the high effluent discharge from storm drainage, industries and flushing of sewage directly into the river by urban settlements. The sampling sites GR12 and GR17 show a high increase in values of COD and BOD₅, which may be due to the presence of pulp industries, sugar industries and thermal power plants in the vicinity of these sampling sites. The overall values meets the environment protection rules established by the Central Pollution Control Board [47], which describes COD and BOD₅ limits of inland surface waters of 250 mg/L and 30 mg/L respectively. However, these values exceeds drinking threshold values, which should be less than 10 mg/L and 5 mg/L in the case of COD and BOD₅, respectively.

The intensity of non-compound, free oxygen present in the river water is called dissolved oxygen (DO). It is an important parameter for investigating water quality because of its impact on organisms living in water. Too low or too high level of DO can affect water quality and endanger aquatic life. The DO values did not show large spatial variations in the Garra River and its tributaries, ranging from 7.38 mg/L to 8.92 mg/L and 7.3 mg/L to 8.67 mg/L, respectively (Fig. 2(b)). This indicates that water quality is not harmful to the aquatic environment.

4.1.1. Concentration of major ions and its possible sources

Li⁺ elements are found in nature mostly in the clay fraction of the soil, potable water, surface water, groundwater and marine

waters as well [48]. In surface waters, the assessment of Li⁺ concentration is often overlooked because it naturally exists at low concentration (usually < 0.04 mg/L; [49, 50]). The concentration of Li⁺ ranged from 0.111 mg/L to 0.54 mg/L, with an average of 0.19 mg/L in the Garra River. However, in the case of tributaries, the range was between 0.114 mg/L to 0.32 mg/L, with an average of 0.16 mg/L. The higher variation in the values of Li⁺ concentration from upstream to downstream (Fig. S3(a)) suggests that the difference in sampling location has a major control over the Li⁺ content. Weathering of rocks such as sandstone and limestone [51] may be responsible for the concentration of Li⁺ in the upper reaches of the Garra River. In the middle and downstream of the river, anthropogenic sources may be the main cause of Li⁺ concentration, including waste disposal and industrial wastewater, as the use of Li⁺ includes pharmaceuticals, synthetic rubber, chemical manufacturing, lubricants and batteries [52].

Through the weathering processes, Na⁺ and K⁺ are washed away from the soil and rocks in the catchment area. Rivers generally contain about 9 mg/L and 2-3 mg/L of Na⁺ and K⁺, respectively; however, these concentrations may fluctuate due to geological conditions and wastewater contamination (<https://www.lenntech.com/periodic/water/>). The concentration of Na⁺ and K⁺ in the Garra River ranged from 3.3 mg/L to 47.4 mg/L and 0.5 mg/L to 11.0 mg/L with an average of 21.2 mg/L and 5.8 mg/L, respectively. As seen from the Fig. S3(b), the concentration of Na⁺ and K⁺ in the upper reaches of the river is not very high and may be dissolved through weathering processes. The middle and lower reaches of the river show a large increase in Na⁺ and K⁺ values, which is the result of human activities, because these regions are densely populated and have more industrial and agricultural activities. Wastewater discharged from industries and agricultural runoff is a possible cause of elevated concentrations of Na⁺ and K⁺. Since, Na⁺ is used in various industrial purposes, such as the chemical industries, it is converted to sodium hydroxide, chlorine gas or sodium carbonate, food industries as a flavouring agent or a preservative, leather and textile industries and in cleanser and soap production. K⁺ is commonly used in synthetic fertilizers, glass production, fluid soap production, medicines, photography tanning, etc.

Multivalent cations and anions are the cause of water hardness, and in most cases, this is due to Mg²⁺ and Ca²⁺. In this study,

Fig. 3. (a) - (f) Spatial variations in F^- , Cl^- , SO_4^{2-} , PO_4^{3-} , NO_3^- and HCO_3^- in water of Garra River and its tributaries.

the Mg^{2+} and Ca^{2+} hardness are expressed as Eq. (1) [46] in terms of the equivalent of calcium carbonate.

$$\text{Hardness (as } CaCO_3) = M^{2+} \times \frac{50}{\text{Eq. Wt. of } M^{2+}} \quad (1)$$

Among them, M^{2+} stands for divalent metallic ion. The total hardness is described as an increase in the hardness of Mg^{2+} and Ca^{2+} , which is 65 to 70 mg/L as $CaCO_3$ in the upstream (GR1, GR2, GR3, GR4) and 75 to 144 mg/L as $CaCO_3$ in the middle and downstream (GR5 to GR20 and T1 to T6) (Fig. 3(f)). *Potasznik and Szymczyk [53] and Chapra et. al. [54] observed that the concentration of Mg^{2+} has been increased in the surface water due to the presence of sedimentary rocks, mainly dolomite. Weathering of rocks such as sandstone may be responsible for the concentration of Mg^{2+} in the upper reaches of the Garra River. WHO [44] classifies hardness ranges >300, 150–300, 75–150 and 0–75 into very hard, hard, moderately hard and soft, respectively. Therefore, the water of the mainstream and its tributaries is in soft to moderately hard category.

The amounts of F^- composition in the upper earth crust is soluble in water; therefore, it is usually present in groundwater and surface waters [55]. Fig. 3(a) shows that the F^- concentrations has a spatial variation ranging from 0.10 mg/L to 0.60 mg/L with an average concentration of 0.27 mg/L. The upstream F^- concentration is lower than downstream of the river, which may be the result of natural sources, such as geological, chemical, physical and the porosity and acidity of the soil and rock. The effect of anthropogenic sources on F^- concentration can be seen in the middle and downstream of the river (Fig. 3(a)), mainly from GR14 to GR20. This may be

due to the presence of coal-burning from the thermal power plant, brick-making industries, and the use of phosphatic fertilizer in agricultural fields [56].

The contents of Cl^- and SO_4^{2-} in the Garra River ranged from 0.43 mg/L to 8.33 mg/L and from 0.97 mg/L to 32.71 mg/L, with an average concentration of 3.42 mg/L and 9.06 mg/L, respectively. From Fig. 3b and 3c, it is evident that the concentrations of Cl^- and SO_4^{2-} in the upstream are lower compared to the downstream of the river and can be attributed to the same reason as F^- . Typically, the SO_4^{2-} and Cl^- ions in the river water are introduced by effluent from the anaerobic wastewater treatment plant and chloride used in the tertiary treatment, respectively. The absence of these wastewater treatment plants may also be a possible cause of Cl^- and SO_4^{2-} concentration throughout entire sampling period. However, the average values of Cl^- and SO_4^{2-} in river water are within the limits specified by BIS [43] and WHO [44].

PO_4^{3-} in rivers is usually the result of runoff from agricultural fields sprayed with fertilizers and effluent discharge from sewage treatment plants [3, 57]. Another anthropogenic source is water containing dissolved detergents which are discharged into the river and increase PO_4^{3-} concentration of the river due to PO_4^{3-} additive (an essential ingredient in detergent). The concentration of PO_4^{3-} in the river ranged from 0.02 mg/L to 1.47 mg/L, with an average of 0.35 mg/L (Fig. 3(d)). Generally, the PO_4^{3-} concentration is found to be higher in the downstream region of the river. These high values of PO_4^{3-} may be the result of agricultural runoff, as the area is dominated by agricultural practices.

The main source of NO_3^- in river is decaying legumes, but the oxidation of animal and human excreta also contribute a lot. In addition, municipal emissions are also a very high contributor,

especially for facilities that do not have a nitrogen removal method. In the Garra River, the NO_3^- concentration ranged from 0.09 mg/L to 14.24 mg/L, with an average concentration of 4.99 mg/L (Fig. 3(e)). The NO_3^- concentration in all samples collected during the campaign was recorded below the BIS [43] and WHO [44] limit of 45 mg/L and 50 mg/L, respectively, for methaemoglobinaemia in children. Therefore, from this perspective, it makes water safe.

The concentration of HCO_3^- in the Garra River ranged from 80.8 mg/L to 193.5 mg/L, with an average concentration of 150.64 mg/L (Fig. 3(f)). In the upper reaches of the river, the concentration of HCO_3^- is mainly attributed to the weathering of silicates and carbonates rock. However, in the middle and downstream regions, these concentrations increase and the effects of anthropogenic activity may be a possible factor.

4.2. Stretch Wise Classification of the River Water

To understand the overall quality of water in the Garra River catchment, the entire basin is divided into four sections, and the water quality parameters of each section are averaged. The initial stretch of the Garra River basin contains rivers flowing through the lower part of the Kumaon Himalayas. The water quality along this stretch was found to be better than the other stretches. The average concentrations of COD and BOD_5 in this section of the river were 15.6 mg/L and 7.4 mg/L, respectively. Compared with other sections, ions like F^- , SO_4^{2-} and NO_3^- in the water collected from this stretch were also found to be the lowest (Table 1). These results can be attributed to relatively few anthropogenic, agricultural and industrial activities in this stretch.

In terms of organic content, the third and fourth sections of the Garra River from Bisalpur to Shahjahanpur and Shahjahanpur to Kannauj were found to be the most polluted. For the mainstream, the average concentrations of COD and BOD_5 in these areas are > 40 mg/L and > 21 mg/L, respectively. Similarly, for tributaries, these values are > 22 mg/L and > 15 mg/L, respectively. The high values in these sections are mainly due to the human influence, because the catchment areas between these regions are densely populated, and there are several industries, such as sugar, paper, thermal power plant, and direct discharge from sewage treatment plants into river.

4.3. Statistical Analysis of the Data

4.3.1. Pair sample t-test

Paired sample t-test, sometimes referred to as dependent sample t-test. This is a statistical procedure used to determine if the average difference between the two sets of perceptions is zero. The results obtained for the t-test are shown in Table S2. Except for Ca^{2+} and HCO_3^- , all other parameters (COD, BOD_5 , F^- , Cl^- , SO_4^{2-} , PO_4^{3-} , NO_3^- , Li^+ , Na^+ , K^+ , and Mg^{2+}) were subjected to the t-test do not show any critical variation in their means. In the t-test, the p-value was found to be higher than the significant value ($p < 0.05$) in case of all parameters except HCO_3^- .

Therefore, we can conclude that there is no direct contributor of organic (COD, BOD_5), nutrient (PO_4^{3-} , NO_3^-), minerals (F^- , Cl^- , SO_4^{2-} , Li^+ , Na^+ , K^+ , Ca^{2+} and Mg^{2+}) content to the mainstream except tributaries water. However, HCO_3^- in the river was more than tributaries (t-static= -3.802 and $p < 0.05$). The difference may

Table 1. Stretch Wise Classification of Water Quality Parameters of Garra River and Its Tributaries

Stretch of river	Adjacent towns/cities	River Sampling Stations	Tributary Sampling Station	Tributaries							Main Garra River						
				pH	HCO_3^- mg/L	COD mg/L	BOD_5 mg/L	NO_3^- mg/L	SO_4^{2-} mg/L	F mg/L	pH	HCO_3^- mg/L	COD mg/L	BOD_5 mg/L	NO_3^- mg/L	SO_4^{2-} mg/L	F mg/L
Kumaon Himalayas	Nainital, Khatima, G1, G2, G3, G4	-	-	-	-	-	-	-	-	-	7.2 $\pm$.40	86.5 $\pm$ 6.8	15.6 $\pm$ 2.9	7.4 $\pm$ 1.4	0.23 $\pm$ 0.05	1.5 $\pm$ 0.52	0.12 $\pm$ 0.02
				-	-	-	-	-	-	-	-	-	-	-	-	-	-
From Nanakmatla to Bisalpur	Majhola, Pilibhit, Navadiya	G5, G6, G7, G8, G9	T1	7.5	121.83	36.09	20.1	2.31	2.85	0.23	7.4 $\pm$ 0.52	148.71 $\pm$ 20.8	22.25 $\pm$ 4.6	11.76 $\pm$ 3.42	0.9 $\pm$ 0.58	5.29 $\pm$ 2.9	0.20 $\pm$ 0.01
				-	-	-	-	-	-	-	-	-	-	-	-	-	-
From Bisalpur to Shahjahanpur	Katra, Tillyhar, Nigohi, Rosa	G10, G11, G12, G13, G14	T2, T3	7.8 $\pm$ 0.3	145.04 $\pm$ 20.8	22.26 $\pm$ 4.6	12.33 $\pm$ 1.07	1.93 $\pm$ 0.03	8.44 $\pm$ 0.75	0.28 $\pm$ 0.06	7.9 $\pm$ 0.2	178 $\pm$ 11.9	40.01 $\pm$ 6.6	21.51 $\pm$ 3.1	1.12 $\pm$ 0.6	13.25 $\pm$ 9.6	0.30 $\pm$ 0.15
				-	-	-	-	-	-	-	-	-	-	-	-	-	-
From Shahjahanpur to Kannauj	Sehramau, Shahabad, Hardoi, Sandi	G15, G16, G17, G18, G19, G20	T4, T5, T6	7.6 $\pm$ 0.27	160.6 $\pm$ 12.2	21.63 $\pm$ 2.18	15.54 $\pm$ 1.8	3.79 $\pm$ 0.45	17.09 $\pm$ 4.8	0.28 $\pm$ 0.03	8.17 $\pm$ 0.4	173.44 $\pm$ 9.6	26.48 $\pm$ 14.5	14.93 $\pm$ 4.7	2.54 $\pm$ 1.2	10.86 $\pm$ 3.2	0.4 $\pm$ 0.13
				-	-	-	-	-	-	-	-	-	-	-	-	-	-

be due to the removal of free and combined carbon dioxide in the river by algae, which produced more carbonate [46].

4.3.2. Hierarchical cluster analysis

In order to finalize the statistical combination of the Garra River sampling sites, HCA was used. The result of this analysis led to a dendrogram (Fig. 4) having a significance at $(Dlink/Dmax) \times 100 < 70$. All 20 sampling locations are ultimately divided into three clusters as there were sampling sites with similar water quality and sources of pollution in these groups, and sufficient water quality information (physical, chemical, nutrient, and organic) was available.

The sampling stations (GR1 to GR8) belong to cluster 1, and pollution level is low. Due to the quiet anthropogenic, agricultural and industrial activities in the region, natural processes such as weathering and rock erosion are the main sources of pollution. Cluster 2 consists of sampling stations (GR9, GR16, GR18, GR19 and GR20) which show high levels of pH, EC, TDS, NO_3^- , PO_4^{3-} , SO_4^{2-} , F, Cl, Li^+ , Na^+ , K^+ , Ca^{2+} , Mg^{2+} and HCO_3^- . However, turbidity, COD and BOD_5 showed low concentration in this cluster. The sampling points belong to this cluster flow in low-lying areas, with point and non-point sources, such as various industrial emissions near HarDOI and Kannauj, agricultural activities, urban sewage and discharge from wastewater treatment plants. Cluster 3 consisting of sampling stations (GR10, GR11, GR12, GR13, GR15 and GR17) showed a lower pollution level than cluster 2 for all parameters, but the turbidity, COD, and BOD_5 concentrations were high in this cluster. The reason for the high concentration of these parameters in this cluster may be due to the discharge of industrial effluents from industries such as paper and pulp, fertilizer, sugar and distillery. The sampling station GR14 does not belong to any cluster and it shows a very high concentration of all parameters. This may be due to the discharge wastewater from the thermal power plant [58] at Rosa town; therefore, it should be sampled separately in future sampling. These results indicate that for grouping of sampling stations, cluster analysis is a useful method

consistent with its interrelated features, thus saving time, cost-effectiveness, and most favourable river sampling in the future. Kim and Mueller [59] and Kazi et al. [60] also used the same procedure in their study to assess potential observed water quality plans.

4.3.3. Source Identification of Pollution by Principal Component Analysis (PCA) and Correlation Matrix

The spatial correlation matrix of the water quality parameters is obtained by PCA, as shown in Table S3. Most of the parameters in Table S3 show a positive correlation with other parameters, except for a few such as Li^+ and DO. Every value shows the changeability of a parameter for another parameter in the matrix, and the underlined values show a high and positive correlation. pH and EC are significantly positively correlated with Mg^{2+} and TDS, respectively. TDS is significantly positively correlated with Ca, HCO_3^- and Cl. COD and BOD are positively correlated with each other. DO and Li^+ do not show any significant correlation with any parameters. NO_3^- shows a good and positive correlation with PO_4^{2-} and Mg^{2+} .

PO_4^{2-} also showed a good and positive correlation with parameters such as Ca, Mg^{2+} , and HCO_3^- . Na^+ is positively correlated with K^+ . Ca is significantly positively correlated with Mg^{2+} and HCO_3^- ; however, Mg^{2+} shows a good and positive correlation with HCO_3^- , F, and Cl. SO_4^{2-} also showed a good and positive correlation with F and Cl. The combined insightful connections between physicochemical parameters indicates that water quality is primarily controlled by carbonate weathering. There are likewise chances of the existence of dolomite, a common source of Mg^{2+} and Ca^{2+} . A significant correlation between F and Ca^{2+} also indicates the presence of minerals like fluorapatite, apatite, and fluorospar. At point scales, geochemistry can be controlled by anthropogenic sources, such as mass bathing and the use of excess fertilizers, and can be revealed by a significant correlations between Cl, SO_4^{2-} and NO_3^- [61]. In this way, it can be seen that anthropogenic, geogenic and natural processes primarily control the hydro-geochemistry of the Garra River.

The scree plot (Fig. S4) was utilized to distinguish the number of principal components (PCs) to understand the basic structure of the data [62]. After the 5th eigenvalue, the slope indicated by scree plot changes significantly. Cattell and Jaspers [63] recommend using each PC and the 1st PC after the break, with the goal of retaining four PCs, whose eigenvalues are more noteworthy than solidarity, and clarify 81.5% of the fluctuations or data contained in the original data set.

Loadings refers to the projection of the original variable on the subspace of the PC and correspond to the correlation coefficient between the variable and the PC. There were three PCs with eigenvalues > 1 , accounting for about 77.61% of the total data set variation. Table 2 shows the loading of six maintained PCs.

PC1 explained a variance of 53.6%, and most parameters such as F, Cl, pH, HCO_3^- , NO_3^- , SO_4^{2-} , PO_4^{2-} , EC, TDS, Ca^{2+} , Mg^{2+} , and BOD were significantly involved (Table 2). The starting point of these variables may be shared and may form the weathering of marl, gypsum and limestone soils. Considering the large amount of oxygen consumed by the increase in dissolved organic matter,

Fig. 4. Dendrogram showing sampling site clusters on the Garra River.

Table 2. Loadings of 17 Experimental Variables on Six Significant Principal Components for 20 River Water Samples

Variable	PC1	PC2	PC3	PC4	PC5	PC6
Mg ⁺	0.912	-0.216	-0.187	0.097	-0.120	-0.104
Cl ⁻	0.868	-0.065	0.034	0.119	0.171	-0.067
TDS	0.866	-0.021	0.430	-0.129	0.157	0.084
HCO ₃ ⁻	0.866	0.041	0.154	0.259	-0.258	-0.124
Ca ⁺	0.861	0.166	0.136	0.335	-0.131	0.085
EC	0.808	-0.030	0.263	-0.254	0.161	0.402
PO ₄ ²⁻	0.789	-0.209	-0.028	0.344	-0.288	0.283
SO ₄ ²⁻	0.766	0.088	-0.283	0.123	<u>0.507</u>	-0.177
BOD	0.737	0.374	-0.242	-0.369	-0.081	0.153
F ⁻	0.730	-0.322	-0.246	0.077	<u>0.468</u>	-0.004
pH	0.726	-0.299	0.028	-0.309	-0.022	-0.437
NO ₃ ⁻	0.721	<u>-0.583</u>	0.067	-0.076	-0.102	0.098
COD	0.647	<u>0.468</u>	-0.214	<u>-0.497</u>	-0.183	0.062
K ⁺	0.629	<u>0.538</u>	0.197	0.017	-0.246	-0.384
Na ⁺	<u>0.540</u>	0.742	0.209	0.129	0.124	0.054
Li ⁻	0.035	0.686	<u>-0.662</u>	0.195	0.009	0.099
DO	<u>-0.438</u>	0.583	<u>0.551</u>	0.056	0.267	-0.017
Eigenvalue	9.110	2.675	1.408	0.966	0.935	0.706
% Variance explained	53.590	15.736	8.285	5.682	5.501	4.152
% Cum. variance	53.590	69.327	77.611	83.293	88.794	92.946

#Bold values denote loadings of interest

the positive loading of COD and BOD₅ in PC1 can be elucidated because organic matter is mainly composed of carbohydrates in urban wastewater, and organic acids. DO have negative participation, and Li⁻ shows positive but not important participation in PC1. PC2 explained a variance of 15.8%, including Na⁺, Li⁻ and DO (positive loading), and NO₃⁻ (negative participation). PC3, PC4 and PC5 explained 8.3%, 5.7% and 5.5% of the total variance, respectively.

4.3.4. Spatial variations in quality of river water by analysis of variance (one-way ANOVA)

The importance of spatial variation in physicochemical parameters between the Garra River and its tributaries and between each sampling location is determined by one-way ANOVA statistical method. When the p value was less than 0.05 ($p < 0.05$), a significant change was considered. Table 3 shows the water sample variations analyzed by ANOVA between the Garra River and its tributaries. Except for turbidity, K⁺, and HCO₃⁻, all other parameters did not show any significant change. The variation in turbidity, K⁺ and HCO₃⁻ may be due to leaching of the rocks along the path of the Garra river, while the tributaries have local flow. However, in the case of spatial variation between each sampling point, a highly significant variation is exhibited by turbidity, NO₃⁻, Na⁺, K⁺, Mg⁺ and HCO₃⁻. Sampling points on the Garra river were intercepted in various tributaries, which may have changed the nature of pollution and the value of pollution parameters.

Table 3. The Result of ANOVA Analysis between the Garra River and Its Tributaries and between Each Sampling Location

Variables	Between Garra River and its tributary	Between each point
pH	NS(P = 0.207)	NS(P = 0.283)
Turbidity (NTU)	** (P = 0.000)	** (P = 0.001)
EC (μS/cm)	NS(P = 0.066)	NS(P = 0.087)
TDS (mg/L)	NS(P = 0.198)	NS(P = 0.066)
COD (mg/L)	NS(P = 0.077)	NS(P = 0.178)
BOD (mg/L)	NS(P = 0.151)	NS(P = 0.058)
DO (mg/L)	NS(P = 0.436)	NS(P = 0.129)
NO ₃ ⁻ (mg/L)	NS(P = 0.066)	** (P = 0.003)
PO ₄ ³⁻ (mg/L)	NS(P = 0.690)	NS(P = 0.081)
Li (mg/L)	NS(P = 0.058)	NS(P = 0.296)
Na (mg/L)	NS(P = 0.094)	* (P = 0.031)
K (mg/L)	* (P = 0.039)	** (P = 0.004)
Ca (mg/L)	NS(P = 0.143)	NS(P = 0.836)
Mg (mg/L)	NS(P = 0.134)	** (P = 0.002)
HCO ₃ (mg/L)	* (P = 0.041)	** (P = 0.004)

#NS=non significant; **= highly significant; *= significant

4.4. Concentration of Heavy Metals

Heavy metal pollution in the river water is one of the most important concerns of rural and urban communities in developing nations. The entry of these toxic heavy metals into the environment may lead to bioaccumulation and biomagnifications [64]. Heavy metals pollution in the riverine environments has received global attention due to its persistence, abundance and environmental toxicity [65, 66]. To observe the concentration of heavy metals in the Garra River, Fe, Zn, and Mn in the collected water samples were analysed in AAS. The analysis showed that all samples contained Fe, Zn and Mn, including mainstream and tributaries.

Fig. 5 (a) and (b) show the concentration of Fe, Zn and Mn in the Garra River and its tributaries. As can be seen from the figure, the concentration of Fe in the mainstream and the tributaries is very high, while the concentrations of Zn and Mn are also high, but lower compared with Fe. The concentration of Fe ranges from 0.205 mg/L to 55.99 mg/L, with an average concentration of 17.31 mg/L in the Garra River. In the case of tributaries, the concentration of Fe is 0.73 mg/L to 51.92 mg/L, with an average concentration of 16.94 mg/L. In case of the Garra River, the concentrations of Zn and Mn ranges from 0.002 mg/L to 0.84 mg/L and 0.01 mg/L to 0.83 mg/L, with an average concentration of 0.14 mg/L and 0.25 mg/L, respectively. However, in the case of tributaries, they are in the range of 0.02 mg/L to 0.18 mg/L and 0.005 mg/L to 0.69 mg/L, with an average concentration of 0.10 mg/L and 0.24 mg/L, respectively.

Fig. 5. Spatial variations in heavy metals (a) Fe and (b) Zn and Mn in water of main stream and its tributaries.

As can be seen from Fig. 5(a) and (b), the concentrations of Fe, Zn and Mn show an increased pattern from upstream to downstream. The upstream Fe concentration is mainly from natural iron sources, which may be due to the presence of silicate rock weathering [67] in the upper part of the basin. The middle stream and downstream of the Garra River and its tributaries are contaminated with medium to high heavy metals at several locations, which may be the results of the dense population (Fig. S1(d)) and high industrial and agricultural activity in these stretches of the Garra basin. The primary anthropogenic sources are the discharge of partially treated and untreated industrial wastewater and sewage containing toxic metals. In addition, it comes from the widespread use of metal chelates in a wide range of industries and pesticides and fertilizers containing heavy metals in the agricultural sector [68, 69]. The average value of Zn in case of the Garra River and its tributaries is much lower than the approved limit of BIS [43]. However, the Fe and Mn concentrations in mainstream and tributaries show high values from the drinking limits recommended by BIS [43] and WHO [44].

5. Conclusions

The study was designed to assess the water quality parameters of the Garra River and its tributaries. The sampling points located downstream of the river show that the concentration of PO_4^{3-} is as high as 0.4 - 0.5 mg/L. The downstream section of the river in GFP from Bisalpur to Shahjahanpur and from Shahjahanpur to Kannauj contains more SO_4^{2-} and organic content compared to the upstream section in GFP and Kumaon hills. A paired sample t-test indicating that HCO_3^- in the river was more than tributaries. Approximately 77% of the total variation can be explained by extracted PC, which has an eigenvalue > 1 and shows the positive and heavy loadings of the river's mineral portion. One-way ANOVA clarified turbidity, K^+ and HCO_3^- are parameters having considerable variation between the Garra River and its tributaries. However, NO_3^- , Na^+ , K^+ , Mg^+ and HCO_3^- are parameters that show significant variation between each location of the Garra River.

Turbidity, Li^+ , HCO_3^- , Fe, and Mn are the most important parameters affecting the water quality of the Garra river. The potential sources of in the Garra River is the dissolution of rocks through chemical and physical weathering processes in the upstream of the river. In the middle and lower reaches of the river, pollution is mainly due to the human influence as the catchment area in between is densely populated. The other sources of pollution in the middle and lower reaches of the river is the presence of various industries, such as sugar industries, paper industries, thermal power plant and sewage discharged directly from sewage treatment plants into rivers. The downstream region of the river containing sample locations from GR9 to GR20 shows high levels of contamination in terms of physicochemical parameters and heavy metals.

These methods can help water quality monitoring agencies to improve current monitoring program(s) by reducing the number of monitoring stations to the ones that best represent the spatial pattern of river water quality. Ultimately, this will help reduce the time, effort, and cost of assessing river water quality.

Some of the limitations in the conclusions drawn from this study may be that large data sets that multivariate techniques need to provide meaningful results are not available. However, as the first study on the Garra River Basin, our research can be used as a case study to further strengthen the research findings of river water quality. In addition, results based on descriptive statistics are also presented in our investigation, which will help to assess comparatively future datasets with this study.

Acknowledgments

We would like to thank to deanship of scientific research (DSR) at King Abdulaziz University (KAU)-Jeddah, Saudi Arabia for providing funding support (D1441-559-145) in completion of this article.

Author Contributions

M.Y.A.K. (Assistant Professor) conducted all the experiments and wrote the manuscript. M.Y.A.K. (Assistant Professor) and J.W. (Research Associate) revised and edited the manuscript.

References

- Manahan SE. Environmental chemistry of water. In: fundamentals of environmental chemistry. 1st ed. Boca Raton, Florida, United States: CRC Press; 1993. p. 373-413.
- Bricker OP, Jones BF. Main factors affecting the composition of natural waters. In: Salbu B Steinnes E, eds. Trace elements in Natural Waters. Boca Raton, Florida, United States: CRC Press; 1995. p. 1-20.
- Carpenter SR, Caraco NF, Correll DL, Howarth RW, Sharpley AN, Smith VH. Nonpoint pollution of surface waters with phosphorus and nitrogen. *Ecol. Appl.* 1998;8(3):559-568.
- Jarvie HP, Whitton BA, Neal C. Nitrogen and phosphorus in east coast British rivers: speciation, sources and biological significance. *Sci. Total Environ.* 1998;210:79-109.
- Khan MY, Khan B, Chakrapani GJ. Assessment of spatial variations in water quality of Garra River at Shahjahanpur, Ganga Basin, India. *Arab. J. Geosci.* 2016a;9(8):516.
- Khan MY, Gani KM, Chakrapani GJ. Assessment of surface water quality and its spatial variation. A case study of Ramganga River, Ganga Basin, India. *Arab. J. Geosci.* 2016b;9(1):28.
- Kumar A, Sharma MP, Taxak AK. Analysis of water environment changing trend in Bhagirathi tributary of Ganges in India. *Desal. Water Treat.* 2017;63:55-62.
- Khan MY, Gani KM, Chakrapani GJ. Spatial and temporal variations of physicochemical and heavy metal pollution in Ramganga River—a tributary of River Ganges, India. *Environ. Earth Sci.* 2017;76(5):231.
- Khan MY, Tian F. Understanding the potential sources and environmental impacts of dissolved and suspended organic carbon in the diversified Ramganga River, Ganges Basin, India. *Proc. Int. Assoc. Hydrol. Sci.* 2018;379:61-66.
- Li Y, Khan MY, Jiang Y, et al. CART and PSO+ KNN algorithms to estimate the impact of water level change on water quality in Poyang Lake, China. *Arab. J. Geosci.* 2019;12(9):287.
- Finnveden G, Hauschild MZ, Ekvall T, et al. Recent developments in life cycle assessment. *J. Environ. Manage.* 2009;91(1):1-21.
- Dixon W, Chiswell B. Review of aquatic monitoring program design. *Water Res.* 1996;30(9):1935-1948.
- Kumar A, Sharma MP, Yadav NS. Assessment of Water Quality Changes at Two Locations of Chambal River: MP. *J. Mater. Environ. Sci.* 2014;5(6):1781-1785.
- Mishra S, Sharma MP, Kumar A. Assessment of Water Quality in Surha Lake Based on Physiochemical Parameters, India. *J. Mater. Environ. Sci.* 2015;6:2446-2452.
- Singh KP, Malik A, Mohan D, Sinha S. Multivariate statistical techniques for the evaluation of spatial and temporal variations in water quality of Gomti River (India)—a case study. *Water Res.* 2004;38(18):3980-3992.
- Ouyang Y, Nkedi-Kizza P, Wu QT, Shinde D, Huang CH. Assessment of seasonal variations in surface water quality. *Water Res.* 2006;40(20):3800-3910.
- Shrestha S, Kazama F. Assessment of surface water quality using multivariate statistical techniques: A case study of the Fuji river basin, Japan. *Environ. Modell. Softw.* 2007;22(4):464-475.
- Razmkhah H, Abrishamchi A, Torkian A. Evaluation of spatial and temporal variation in water quality by pattern recognition techniques: a case study on Jajrood River (Tehran, Iran). *J. Environ. Manage.* 2010;91(4):852-860.
- Zhao J, Fu G, Lei K, Li Y. Multivariate analysis of surface water quality in the Three Gorges area of China and implications for water management. *J. Environ. Sci.* 2011;23(9):1460-1471.
- Bu H, Meng W, Zhang Y. Spatial and seasonal characteristics of river water chemistry in the Taizi River in Northeast China. *Environ. Monit. Assess.* 2014;186(6):3619-3632.
- Tanos P, Kovács J, Kovács S, Anda A, Hatvani IG. Optimization of the monitoring network on the River Tisza (Central Europe, Hungary) using combined cluster and discriminant analysis, taking seasonality into account. *Environ. Monit. Assess.* 2015;187(9):575.
- Bonansea M, Ledesma C, Rodriguez C, Pinotti L. Water quality assessment using multivariate statistical techniques in Río Tercero Reservoir, Argentina. *Hydrol. Res.* 2015;6(3):377-388.
- Phung D, Huang C, Rutherford S, et al. Temporal and spatial assessment of river surface water quality using multivariate statistical techniques: a study in Can Tho City, a Mekong Delta area, Vietnam. *Environ. Monit. Assess.* 2015;187(5):229.
- Varekar V, Karmakar S, Jha R. Seasonal rationalization of river water quality sampling locations: a comparative study of the modified Sanders and multivariate statistical approaches. *Environ. Sci. Pollut. R.* 2016;23(3):2308-2328.
- Gangapedia. About us: Gangapedia. Retrieved Dec 20, 2013, Available from <http://gangapedia.iitk.ac.in/?q=content/about-us>
- Kazmi AA, Hansen IS. Numerical models in water quality management: a case study for the Yamuna river (India). *Water Sci. Technol.* 1997;36(5):193.
- Singh KP, Malik A, Sinha S. Water quality assessment and

- apportionment of pollution sources of Gomti river (India) using multivariate statistical techniques—a case study. *Anal Chim Acta*. 2005;538(1-2):355-374.
28. Mishra S, Kumar A, Shukla P. Study of water quality in Hindon River using pollution index and environmetrics, India. *Desalination Water Treat*. 2016;57(41):19121-19130.
 29. Mishra S, Kumar A, Shukla P. Study of water quality in Hindon River using pollution index and environmetrics, India. *Desalin. Water Treat*. 2016;57(41):19121-19130.
 30. Parmar KS, Bhardwaj R. Statistical, time series, and fractal analysis of full stretch of river Yamuna (India) for water quality management. *Environ. Sci. Pollut. R*. 2015;22(1):397-414.
 31. Sharma D, Kansal A, Pelletier G. Water quality modeling for urban reach of Yamuna river, India (1999–2009), using QUAL2Kw. *Appl. Water Sci*. 2017;7(3):1535-1559.
 32. Khan MY, Chakrapani GJ. Particle size characteristics of Ramganga catchment area of Ganga River. In: *Geostatistical and geospatial approaches for the characterization of natural resources in the environment 2016*; pp. 307-312. Springer, Cham
 33. Khan MY, Daityari S, Chakrapani GJ. Factors responsible for temporal and spatial variations in water and sediment discharge in Ramganga River, Ganga Basin, India. *Environ. Earth Sci*. 2016c;75(4):283.
 34. Khan MY, Hasan F, Panwar S, Chakrapani GJ. Neural network model for discharge and water-level prediction for Ramganga River catchment of Ganga Basin, India. *Hydrolog Sci. J*. 2016d;61(11):2084-2095.
 35. Khan MY. Spatial variation in the grain size characteristics of sediments in Ramganga River, Ganga Basin, India. *Handbook of environmental materials management*. Springer, Berlin. 2018
 36. Daityari S, Khan MY. Temporal and spatial variations in the engineering properties of the sediments in Ramganga River, Ganga Basin, India. *Arab. J. Geosci*. 2017;10(6):134.
 37. Khan MY, Tian F, Hasan F, Chakrapani GJ. Artificial neural network simulation for prediction of suspended sediment concentration in the River Ramganga, Ganges Basin, India. *Int. J. Sediment Res*. 2019a;34(2):95-107.
 38. Khan MY, Hasan F, Tian F. Estimation of suspended sediment load using three neural network algorithms in Ramganga River catchment of Ganga Basin, India. *Sustain. Water Resour. Manag*. 2019b;5(3):1115-1131.
 39. Khan MY, Hu H, Tian F, Wen J. Monitoring the spatio-temporal impact of small tributaries on the hydrochemical characteristics of Ramganga River, Ganges Basin, India. *Int. J. River Basin Manag*. 2019c;1-1.
 40. Gupta RP, Joshi BC. Landslide hazard zoning using the GIS approach—a case study from the Ramganga catchment, Himalayas. *Eng. Geol*. 1990;28(1-2):119-131.
 41. Khan AU, Rawat BP. Quaternary geology and geomorphology of a part of Ganga basin in parts of Bareilly, Badaun, Shahjahanpur and Pilibhit district, Uttar Pradesh. 1992 Geological Survey of India (GSI).
 42. American Public Health Association (APHA). AWWA and WPCF Standard Methods for the Examination of Waters and Waste Waters. 20th ed. Washington DC; 1998.
 43. Bureau of Indian Standards (BIS: 10500). Indian standard specification for drinking water. Second Revision. New Delhi; 1989.
 44. World Health Organization (WHO). Guidelines for drinking water quality: recommendations, 3rd edn. Geneva; 2008.
 45. Rao CS, Rao BS, Hariharan AV, Bharathi NM. Determination of water quality index of some areas in Guntur district Andhra Pradesh. *Int. J. Appl. Biol. Pharm. Technol*. 2010;1(1):79-86.
 46. Sawyer CN, McCarty PL, Parkin GF. Chemistry for environmental engineering and science. New York: McGraw-Hill; 2003.
 47. Central Pollution Control Board (CPCB). The Environment (Protection) Rules. Schedule – VI., Ministry of Water Resources, Government of India, New Delhi; 1986.
 48. Kostik V, Bauer B, Kavrakovski Z. Lithium content in potable water, surface water, ground water, and mineral water on the territory of Republic of Macedonia. *Int. J. Med. Public Health*. 2014;4(3).
 49. Hill BR, Gilliom RJ. Streamflow, dissolved solids, suspended sediment, and trace elements, San Joaquin River, California, June 1985–September 1988. US Department of the Interior, US Geological Survey; 1993.
 50. Tanner DQ. Surface-water-quality Assessment of the Lower Kansas River Basin, Kansas and Nebraska: Distribution of Trace-element Concentrations in Dissolved and Suspended Phases, Streambed Sediment, and Fish Samples, May 1987 Through April 1990. US Department of the Interior, US Geological Survey; 1995.
 51. Vine JD, Dooley JR Jr. Where on earth is all the lithium? With a section on uranium isotope studies, Fish Lake Valley, Nevada, United States Geological Survey open-file report 80-1234, Denver: Colorado; 1980.
 52. Kszos LA, Stewart AJ. Review of lithium in the aquatic environment: distribution in the United States, toxicity and case example of groundwater contamination. *Ecotox*. 2003;12(5):439-47.
 53. Potasznik A, Szymczyk S. Magnesium and calcium concentrations in the surface water and bottom deposits of a river-lake system. *J. Elem*. 2015;20(3).
 54. Chapra SC, Dove A, Warren GJ. Long-term trends of Great Lakes major ion chemistry. *J. Great Lakes Res*. 2012;38(3):550-560.
 55. Frencken, J.E. (editor). Endemic Fluorosis in developing countries, causes, effects and possible solutions. Publication number 91.082, NIPG-TNO, Leiden, The Netherlands; 1992.
 56. Jha SK, Mishra VK, Sharma DK, Damodaran T. Fluoride in the environment and its metabolism in humans. In: *Reviews of Environmental Contamination and Toxicology*. Springer New York; 2011. p. 121-142.
 57. Wiens JH. Agricultural Runoff and Water Pollution. *Can Water Resour J*. 1980;5(3):78-89.
 58. Baba A, Kaya A, Birsoy YK. The effect of Yatagan thermal power plant (Mugla, Turkey) on the quality of surface and ground waters. *Water Air Soil Poll*. 2003;149(1-4):93-111.
 59. Kim JO, Mueller CW. Introduction to factor analysis: what it is and how to do it. Quantitative applications in the social sciences series. Newbury Park: Sage University Press; 1978.
 60. Kazi TG, Arain MB, Jamali MK, et al. Assessment of water quality of polluted lake using multivariate statistical techniques: A case study. *Ecotox. Environ. Safe*. 2009;72(2):301-9.
 61. Avtar R, Kumar P, Singh CK, et al. Hydrogeochemical assessment of groundwater quality of Bundelkhand, India using statistical approach. *Water Qual. Expos. Hea*. 2013;5(3):105-15.

62. Jackson JE. A User's Guide to Principal Components. Wiley, New York; 1991.
63. Cattell RB, Jaspers J. A general plasmode (No. 30-10-5-2) for factor analytic exercises and research. *Mult. Behav. Res. Monog.* 1967;67:1:212-266.
64. Paul D. Research on heavy metal pollution of river Ganga: A review. *Ann. Agric. Sci.* 2017;15(2):278-286.
65. Ahmed MK, Baki MA, Islam MS, et al. Human health risk assessment of heavy metals in tropical fish and shellfish collected from the river Buriganga, Bangladesh. *Environ. Sci. Pollut. Res.* 2015;22(20):15880-15890.
66. Islam MS, Ahmed MK, Habibullah-Al-Mamun M, Hoque MF. Preliminary assessment of heavy metal contamination in surface sediments from a river in Bangladesh. *Environ. Earth Sci.* 2015;73(4):1837-1848.
67. Krachler R, Jirsa F, Ayromlou S. Factors influencing the dissolved iron input by river water to the open ocean. *Biogeosciences* 2005;2(4):311-315.
68. Abbasi SA, Abbasi N, Soni R. Heavy Metals in the Environment. New Delhi: Mittal Publications; 1998.
69. Reza R, Singh G. Heavy metal contamination and its indexing approach for river water. *Int. J. Environ. Sci. Technol.* 2010;7(4):785-792.