Experimental study on adsorption characteristics of Cu^{2+} and Zn^{2+} by datong lignite

Sihang Bao¹, Junzhen Di^{2*}, Jianguo Yang³, Donglin Wang⁴, Juan Sun², Yanrong Dong²

¹College of Mining, Liaoning Technical University, Fuxin 123000, China

²College of Civil Engineering, Liaoning Technical University, Fuxin 123000, China

³Anhui Shui'an Construction Group Co., Ltd., Hefei, 230601, China

⁴College of Civil Engineering, Anhui Jianzhu University, Hefei, 230601, China

ABSTRACT

In view of the high content of Cu^{2+} and Zn^{2+} in acid mine drainage (AMD), the adsorption properties of lignite for Cu^{2+} and Zn^{2+} were studied. The adsorption performance of lignite for Cu^{2+} and Zn^{2+} was revealed by combining with FT-IR, XPS and EDS. The results showed that the adsorption kinetic model of lignite for Cu^{2+} and Zn^{2+} conformed to the quasi-first-order kinetic model. The isothermal adsorption line fitting models of lignite for Cu^{2+} and Zn^{2+} were in accordance with the Langmuir model and the Freundlich model, respectively. The maximum equilibrium adsorption capacities of lignite for Cu and Zn were 67.84 mg/g and 55.5 mg/g. The adsorption process of Cu^{2+} and Zn^{2+} by lignite involved electrostatic, coordination and ion exchange. Under the condition of coexistence of two kinds of ion, the adsorption site of lignite had stronger binding ability to copper ions.

Keywords: Adsorption kinetics, Adsorption mechanism, Cu^{2+} , Lignite, Zn^{2+}

1. Introduction

Mineral resources are indispensable means of production for human development. Due to unreasonable development and lack of effective supervision, a large number of mine wastewater discharges, which accounts for about 10% of China's industrial wastewater discharge [1]. Mine wastewater is the general term of natural leaching water, mineral processing wastewater, overflow water of mineral processing waste dam and leaching water of slag accumulation field [2]. Mine wastewater can be divided into AMD [3] and Alkaline Mine Wastewater [4] according to acidity and alkalinity. Direct discharge of mine wastewater without treatment will not only cause serious pollution to the surrounding groundwater and surface water [5], but also cause serious damage to the local ecosystem, especially the damage of AMD to the environment [6]. AMD has a low pH value and contains high concentration of sulfate and many kinds of toxic heavy metal ions (such as Fe, Al, Mn, Pb, Zn, Cu, Cd, Ni, Hg, As, Cr and other heavy metal ions) [7-9]. At present, the common treatment methods for AMD include the physical method, the chemical method

and the biological method [10]. Physical methods include ion exchange, adsorption, membrane filtration, coagulation and flocculation, flotation and electrochemical methods. Chemical methods include alkali neutralization precipitation and sulfide precipitation. Biological methods include constructed wetland method and microbial method [11]. In the actual treatment process, the cost of physical and chemical treatment of AMD is high, and it is extremely easy to cause secondary pollution [12]. Constructed wetland method covers a large area, and is vulnerable to seasonal climate [8]. As a result of its harmless and economic characteristics, microbial method is currently the most promising and concerned treatment method for AMD treatment [12]. Microbial method uses organic matter as carbon source and energy through sulfate-reducing bacteria (SRB) in anaerobic conditions to reduce SO_4^{2-} to S^{2-} . S^{2-} and metal ions in wastewater generate sulfide precipitation to remove sulfate and heavy metal ions in AMD [13]. However, in the actual treatment process, the acid conditions of AMD inhibit the growth of SRB and the heavy metal ions in AMD have toxic effects on SRB [14], resulting in low growth activity of SRB and low treatment efficiency of

This is an Open Access article distributed under the terms of the Creative Commons Attribution Non-Commercial License (<http://creativecommons.org/licenses/by-nc/3.0/>) which permits unrestricted non-commercial use, distribution, and reproduction in any medium, provided the original work is properly cited.

Copyright © 2022 Korean Society of Environmental Engineers

Received January 15, 2021 Accepted April 19, 2021

* Corresponding author

E-mail: dijunzhen@126.com

Tel: +86-13941889524

ORCID: 0000-0002-3608-9436

AMD. Therefore, it is the key to look for a material that can improve AMD pH and adsorb heavy metal ions to repair SRB efficiently.

Lignite reserves are abundant in China. It has been proved that the reserves are about 130 billion tons, accounting for 13% of the national coal resources. Most of them are located in the shallow surface and are easy to be mined [15]. Lignite is a kind of coal whose coalification degree is between peat and bituminous coal. It is rich in humic acid, and its humic acid content is generally between 10% and 80% [16]. Humic acid in lignite is a kind of polyelectrolyte with negative charge, which can adsorb heavy metal ions in AMD by electrostatic attraction. The developed pore structure and specific surface area of lignite provide abundant active sites for heavy metal ions [17]. At the same time, lignite has natural porous properties [18] and large specific surface area. The surface contains active groups such as carboxyl, alcohol hydroxyl, phenol hydroxyl, quinone, carbonyl and methoxy groups [17]. The active groups on the surface of lignite can adsorb heavy metal ions on the surface of lignite by ion exchange and coordination, which is negatively charged [19, 20] and has good affinity for H^+ and heavy metal ions. It can improve the pH of AMD and remove heavy metal ions in AMD. H. Polat *et al.* [21] showed that the adsorption capacity per unit surface area of lignite was at least four times that of activated charcoal. M. Uçurum [22] used lignite to remove heavy metal Pb in water. The results showed that 80 mesh lignite had the best adsorption effect on Pb, and the best adsorption capacity was 29.92 mg/g. Qiongqiong He [23, 24] used lignite as an effective low-cost adsorbent to remove organic pollutants from wastewater. Mohan [25] used lignite to adsorb and remove Fe^{2+} , Fe^{3+} and Mn^{2+} heavy metal ions in AMD. The recovered heavy metal ions were resolved by 0.1 mol/L nitric acid, and the recovery rate of heavy metals was 100%. The adsorption capacity of the lignite can be recovered after the analysis. Fethiye *et al.* [26] studied the kinetic and thermodynamic parameters of Cr(III) adsorption on lignite from Turkey and Anatolia. The experimental results showed that the adsorption rate of Cr(III) reached 90% at pH = 4.5. However, the water quality report of AMD in a coal mine in Datong, Shanxi Province, China showed that the content of Cu^{2+} and Zn^{2+} in the wastewater was high (pH = 3~5, Cu^{2+} = 55~63 mg/L and Zn^{2+} = 77~80 mg/L). The local lignite has the characteristics of large reserves and convenient utilization. Therefore, it is convenient to use local lignite to treat AMD for large-scale application in mining area.

In view of the high content of Cu and Zn in AMD, this experiment used lignite as raw material to explore the adsorption capacity of lignite for Cu^{2+} and Zn^{2+} in AMD. The adsorption characteristics of Cu^{2+} and Zn^{2+} on lignite were analyzed by adsorption kinetics and isothermal adsorption experiments. The competitive adsorption mechanism of Cu^{2+} and Zn^{2+} on lignite was revealed by the adsorption effect of copper and zinc on lignite in single metal and binary metal systems. The lignite before and after AMD adsorption was characterized and analyzed to reveal the internal mechanism of adsorption of Cu^{2+} and Zn^{2+} by lignite, by combining with FT-IR and XPS, so as to provide new methods for the efficient repair of AMD by lignite-assisted SRB.

2. Materials and Methods

2.1. Experimental Materials and Instruments

Experimental materials : lignite raw materials used in the experiment were from Shanxi Fuhong Mineral Products Co., Ltd. The lignite included 52% of humic acid. After crushing lignite with high-speed crusher (HD-ZK), lignite with particle size of 80 mesh was selected for standby. Dry lignite samples were taken for SEM and BET detection. Among them, SEM was detected by ZEISS Sigma 300 instrument, and BET was detected by MIKE ASAP 2460 instrument. SEM detection was shown in Fig. 1. BET results showed that the Langmuir surface area, BET surface area, pore area and average pore diameter of lignite were 48.60, 6.72, 5.64 and 6.72 m^2/g , respectively.

Water quality detection methods and instruments : PHS-3C pH meter was used for pH measurement. Copper and zinc ion concentrations were determined by flame atomic spectrophotometer Z-2000. Turbidity was measured by V-1600PC visible spectrophotometer. Zeta potential measurement was measured by ZS90 Zeta potentiometer. EDS detection was measured by ZEISS Sigma 300. The lignite before and after the experiment was dried in a 105°C blast dryer for 24 h, and then grinded to 200 mesh with quartz bowl. The grinded lignite was evenly mixed with KBr at the ratio of 1%, and the mixture was pressed. The FTIR surface functional groups of the tablet were detected by Nicolet iS50 and Nicolet Nexus410 FT-IR Fourier transform infrared spectrometer. The detection range of FTIR is 4,000~400 cm^{-1} . The crushed lignite was pressed and placed in Bruker D8 Advance X-ray photoelectron spectrometer for XPS detection.

Fig. 1. SEM image of lignite.

2.2. Experimental Method

2.2.1. Adsorption characteristics of lignite in single metal system

Adsorption kinetics experiment of lignite on Cu^{2+} and Zn^{2+} : Analytically reagent $CuSO_4 \cdot 5H_2O$ and $ZnSO_4 \cdot 7H_2O$ were used to prepare Cu^{2+} standard solution and Zn^{2+} standard solution. The Cu^{2+} standard solution (Zn^{2+} standard solution) was taken with a liquid gun (JOANLAB) and filtered by 0.45 μm microporous

membrane. The concentrations of Cu^{2+} and Zn^{2+} in Cu^{2+} standard solution and Zn^{2+} standard solution were determined to be 400 mg/L, and the pH was adjusted to 4 with 1 mol/L diluted HNO_3 . 2 g of lignite was added respectively, after sealing, placed in 150 r/min constant temperature gas bath shaker at 25°C to oscillate. Samples were taken in the minute of 15, 30, 60, 120, 180, 240, 300, 360, 480, 1,320, 1,380, 1,440, 1,500 with a liquid-shift gun, respectively. The samples were filtered by 0.45 μm microporous membrane, and the pH value and the concentrations of Ca^{2+} , Cu^{2+} , Zn^{2+} were determined.

Isothermal adsorption experiment of lignite for Cu^{2+} and Zn^{2+} : Cu^{2+} standard solution and Zn^{2+} standard solution were prepared by analytical pure $\text{CuSO}_4 \cdot 5\text{H}_2\text{O}$ and $\text{ZnSO}_4 \cdot 7\text{H}_2\text{O}$. The Cu^{2+} standard solution (Zn^{2+} standard solution) was taken with a liquid transfer gun and filtered by 0.45 μm microporous membrane. The concentrations were determined to be 1600 mg/L. The above standard solutions were diluted to 800, 640, 320, 160, 80, 40, 20, 10 and 5 mg/L and the pH was adjusted to 4 of all solutions. 1 g of lignite was added to 100 mL of Cu^{2+} and Zn^{2+} solutions with concentrations of 1,600, 800, 640, 320, 160, 80, 40, 20, 10 and 5 mg/L, respectively. After sealing, it was placed in a constant temperature gas bath shaker at 25°C and 150 r/min for 24 h. At 24 h, the samples were sampled with a liquid gun and filtered through a 0.45 μm microporous membrane to measure the concentrations of Ca^{2+} , Cu^{2+} and Zn^{2+} . After the reaction was terminated, the pH value was measured, and the turbidity was measured after standing for 2.5 h.

2.2.2. Adsorption characteristics of lignite in binary metal system

The analytical pure $\text{CuSO}_4 \cdot 5\text{H}_2\text{O}$ and $\text{ZnSO}_4 \cdot 7\text{H}_2\text{O}$ were used to prepare the standard solution with Cu^{2+} and Zn^{2+} concentrations of 1,600 mg/L. The above standard solutions were diluted to 800, 640, 320, 160, 80, 40, 20, 10 and 5 mg/L and the pH was adjusted to 4 of all solutions. 1 g of lignite was added to 100 mL Cu^{2+} and Zn^{2+} solutions of 1,600, 800, 640, 320, 160, 80, 40, 20, 10 and 5 mg/L, respectively. After sealing, the lignite was placed in a constant temperature gas bath shaker at 25°C and 150 r/min for 24 h. At 24 h, the samples were taken with a liquid gun and filtered through a 0.45 μm microporous membrane to determine the concentrations of Ca^{2+} , Cu^{2+} and Zn^{2+} . After the end of the reaction, pH was determined, and turbidity was determined after standing for 2.5 h.

2.2.3. Pollutant leaching experiment of lignite after adsorption of Cu^{2+} and Zn^{2+}

The lignite samples after adsorption of 800 mg/L Cu^{2+} and Zn^{2+} were dried in an air dryer at 105°C for 24 h. 0.5 g of lignite after adsorption of Cu^{2+} and Zn^{2+} was placed in 100 mL deionized water, at 200 r/min and 25 °C oscillation for 24 h. The pH value of leaching solution, the concentration of Cu^{2+} and Zn^{2+} were

determined, and the feasibility of secondary utilization of lignite after adsorption of Cu^{2+} and Zn^{2+} was analyzed.

3. Results and Discussion

3.1. Adsorption Kinetics of Lignite on Cu^{2+} and Zn^{2+}

In order to further explore and analyze the process of lignite adsorption on Cu^{2+} and Zn^{2+} , the adsorption kinetics experiments of lignite adsorbing Cu^{2+} and Zn^{2+} were carried out in single metal system. The experimental results were fitted by using quasi-first-order kinetics and quasi-second-order kinetics model [27]. The fitting results are shown in Fig. 2(a) and Table 1.

The quasi-first-order dynamic model is :

$$\frac{dq_t}{dt} = K_1(q_e - q_t) \quad (1)$$

Where,

q_t : adsorption time is the adsorption quantity at time t, mg/g

q_e : adsorption amount at adsorption equilibrium, mg/g

t : adsorption time, min

K_1 : quasi-first-order kinetic reaction rate constant, 1/min

The quasi-second-order dynamic model is:

$$\frac{dq_t}{dt} = K_2(q_e - q_t)^2 \quad (2)$$

Where,

q_t : adsorption time is the adsorption quantity at time t, mg/g

q_e : adsorption amount at adsorption equilibrium, mg/g

t : adsorption time, min

K_2 : quasi-second-order kinetic reaction rate constant, 1/min

As shown in Fig. 2(a), the adsorption of Cu^{2+} by lignite reached the adsorption equilibrium at 24 h, and the adsorption of Zn^{2+} reached the adsorption equilibrium at 6 h. The adsorption of Cu^{2+} and Zn^{2+} by lignite were basically divided into three stages : rapid adsorption stage, slow adsorption stage and equilibrium adsorption stage. In the first 30 min, because of the rich adsorption sites on the surface of lignite, lignite adsorbed Cu^{2+} and Zn^{2+} rapidly, which was called a rapid adsorption stage. With the progress of adsorption, the adsorption sites on lignite surface gradually decreased, and the adsorption rate gradually decreased. But it was still greater than the desorption rate. The adsorption amount slowly increased with time, and the adsorption entered the slow adsorption stage. At 24h and 6h, the adsorption rate of Cu^{2+} and Zn^{2+} by lignite was equal to the desorption rate, and the adsorption capacity was basically stable. The adsorption

Table 1. Kinetic Parameters for Adsorption of Cu^{2+} and Zn^{2+} by Lignite

	Quasi-first-order kinetic fitting			Quasi-second-order kinetic fitting		
	q_e	K_1	R^2	q_e	K_2	R^2
Cu^{2+}	63.33427	0.03309	0.94098	58.11306	4.12306E45	0.67693
Zn^{2+}	51.85517	0.04066	0.9503	48.29604	-3.30029E27	0.7272

was in a dynamic equilibrium, and the adsorption reached the equilibrium adsorption stage. The equilibrium adsorption capacity of lignite for Cu^{2+} and Zn^{2+} were 67.84 mg/g and 55.5 mg/g, respectively. The higher specific surface area and developed pore structure were the main reasons for the better adsorption performance of lignite.

From Table 1, the correlation coefficient R^2 of the pseudo-first-order kinetic equation of Cu^{2+} and Zn^{2+} adsorption by lignite was large, and the theoretical equilibrium adsorption q_e of Cu^{2+} and Zn^{2+} by lignite calculated by the pseudo-first-order kinetic model was close to the experimental equilibrium adsorption. The correlation coefficient R^2 of the pseudo-second-order kinetic equation was low, and the theoretical equilibrium adsorption q_e was much lower than the experimental equilibrium adsorption. Therefore, the adsorption kinetics of lignite for Cu^{2+} and Zn^{2+} were more in line with the quasi-first-order kinetic model. The pseudo-first-order kinetic model assumes that the adsorbate was physical adsorption, so physical adsorption was the main mechanism of lignite adsorption of Cu^{2+} and Zn^{2+} . The equilibrium adsorption capacities of lignite for Cu^{2+} and Zn^{2+} were 67.84 mg/g and 55.5 mg/g, respectively. The adsorption rates of lignite for Cu^{2+} and Zn^{2+} were 0.033 min^{-1} and 0.041 min^{-1} , respectively. From Fig. 2(b), the calcium ion concentration and solution alkalinity released by lignite were significantly higher when copper is adsorbed. It showed that Cu^{2+} was easier to ion exchange with calcium ions in lignite. The equilibrium adsorption capacity of lignite for Cu^{2+} was higher than that for Zn^{2+} , but the adsorption rate of lignite for Zn^{2+} was higher than that for Cu^{2+} , indicating that the selectivity of lignite for Cu^{2+} was better than that of Zn^{2+} . Covelo et al. [28] found that the adsorption of Cu by humus conformed to the pseudo-first-order kinetic model, and the equilibrium adsorption amount of Cu was about $6\sim 7 \mu\text{mol/g}$, and that of Zn was about $0\sim 2 \mu\text{mol/g}$. Runhu Zhang[29] showed that the maximum adsorption capacity of lignite for Cr^{6+} was 24.96 mg/g. Sohan Shrestha[30] and other studies have shown that the maximum saturated adsorption capacity of activated carbon fiber (lignite and coconut shell-based activated carbon fiber) prepared by lignite combined with coconut shell for Zn^{2+} was 9.43 mg/g. Compared with the above studies, the adsorption of copper and zinc by lignite was significantly better than that of activated carbon fiber prepared by humus and lignite combined with coconut shell.

3.2. Isothermal Adsorption Lines of Lignite on Cu^{2+} and Zn^{2+}

In order to further explore the equilibrium mechanism of lignite

adsorption on Cu^{2+} and Zn^{2+} , the isothermal adsorption experiments of lignite adsorption on Cu^{2+} and Zn^{2+} were carried out in single metal and binary metal systems, respectively. The Langmuir isotherm model and Freundlich isotherm model [31] were used to fit the isothermal adsorption line. The adsorption isotherms of Cu^{2+} and Zn^{2+} of lignite were fitted by Langmuir isotherm model and Freundlich isotherm model. The fitting results are shown in Fig. 2(c)~(e) and Table 2.

Langmuir isotherm model :

$$q_e = \frac{K_L q_m C_e}{1 + K_L C_e} \quad (3)$$

Where,

q_e : adsorption capacity at equilibrium, mg/g

q_m : theoretical maximum adsorption capacity, mg/g

C_e : solution adsorbate concentration at adsorption equilibrium, mg/L

K_L : Langmuir constant, L/mg

Freundlich isotherm model :

$$q_e = K_F C_e^{\frac{1}{n}} \quad (4)$$

Where,

q_e : adsorption capacity at equilibrium, mg/g

C_e : solution adsorbate concentration at adsorption equilibrium, mg/L

K_F : adsorption constant, $(\text{mg/g})(1/\text{mg})^{1/n}$

n : Adsorption strength constant

From Fig. 2(c), according to the isotherm classification system [32], the isothermal adsorption lines of lignite adsorbing Cu^{2+} and Zn^{2+} in single metal and binary metal systems were all L-2 curves in typical L-type isotherms. Junting Sun [33] explored the adsorption of Pb, Cu, Zn, Cd, and Cr by porous carbon (HPC), and the results showed that the adsorption process of the five metals conformed to the Langmuir isotherm. The maximum adsorption capacity of HPC for Cu was 56.4 mg/g. Lijun Wang et al. [34] explored the adsorption of Cu, Pb and Cd by bagasse. The results showed that Langmuir isotherm could describe the adsorption of metal ions well by bagasse. Meanwhile, the results showed that the maximum adsorption capacity of bagasse for Cu^{2+} was 21.98 mg/g. Compared with the above studies, the equilibrium adsorption capacity of

Table 2. Fitting Parameters of Isothermal Adsorption Lines of Lignite for Cu^{2+} and Zn^{2+} under Single Metal and Binary Metal Systems

	Langmuir model			Freundlich model		
	q_m	K_L	R^2	$1/n$	K_F	R^2
Cu^{2+}	228.59014	1.65055E-4	0.9995	0.80948	0.32402	0.99293
Zn^{2+}	163.91855	5.57445E-4	0.99619	0.70469	0.50496	0.98866
Cu^{2+} in binary metal system	200.8214	4.9791E-4	0.99979	0.71248	0.51993	0.99564
Zn^{2+} in binary metal system	5,603.84788	8.96106E-5	0.97123	0.58296	0.50632	0.97125

Cu^{2+} and Zn^{2+} by lignite was 67.84 mg/g and 55.5 mg/g. The adsorption effect of lignite was significantly better than that of porous carbon and bagasse, and it was more convenient to obtain lignite in the mining area when treating AMD. The isothermal adsorption lines of Cu^{2+} and Zn^{2+} adsorbed by lignite in single metal and binary metal systems did not reach an obvious equilibrium, indicating that at the initial concentration set in the experiment, lignite did not show a limited adsorption capacity for Cu^{2+} and Zn^{2+} . Therefore, lignite in single metal and binary metal systems had good adsorption properties for Cu^{2+} and Zn^{2+} . With the increase of the initial concentrations of Cu^{2+} and Zn^{2+} , the equilibrium adsorption capacity of lignite on Cu^{2+} and Zn^{2+} gradually increased. The main reason is that the larger the initial concentrations of

Cu^{2+} and Zn^{2+} in the system are, the larger the concentration difference of Cu^{2+} and Zn^{2+} in the solid phase and liquid phase is. Thus the driving force for the migration of Cu^{2+} and Zn^{2+} to the surface of lignite increased. Therefore, the equilibrium adsorption capacity became larger with the enhanced adsorption capacity of lignite.

The equilibrium adsorption capacity of lignite on Cu^{2+} and Zn^{2+} in single metal system was higher than that of lignite on Cu^{2+} and Zn^{2+} in binary metal system, indicating that there was competition between Cu^{2+} and Zn^{2+} in binary metal system. Mahamadi C et al. [35] showed that the adsorption characteristics of single-element system and multi-element system were different. Sejin Oh [36] and other studies showed that the adsorption effect of activated

Fig. 2. Kinetic and isothermal fitting of Cu^{2+} and Zn^{2+} adsorption by lignite (a) Kinetic fitting of Cu^{2+} and Zn^{2+} adsorption by lignite (b) pH and Ca^{2+} released after adsorption by lignite (c) Isothermal adsorption lines of Cu^{2+} and Zn^{2+} adsorption by lignite in single metal and binary metal systems (d) Adsorption isotherm fitting of Cu^{2+} adsorption by lignite in single metal and binary metal systems (e) Adsorption isotherm fitting of Zn^{2+} adsorption by lignite in single metal and binary metal systems (f) Changes of pH after adsorption of Cu^{2+} and Zn^{2+} by lignite (g) Changes of Ca^{2+} and turbidity after adsorption of Cu^{2+} and Zn^{2+} by lignite (h) Leaching of pollutants from lignite after adsorption of Cu^{2+} and Zn^{2+} .

carbon on Co, Ni and Cu in single metal system was better than that in multi-metal system. This was due to the coexistence of components in the system competitive adsorption sites of adsorbent. The affinity order of lignite on Cu^{2+} and Zn^{2+} was: $\text{Cu}^{2+} > \text{Zn}^{2+}$. At the same time, the surface charge of lignite was negative. The zeta potential measurement results showed that the surface potential of lignite was -18.4 at pH = 7. K.B. Thapa [19] measured the zeta potential of lignite about -15. The zeta potential of lignite measured by Yanan Tu [20] was about -29. The zeta potential of lignite used in this study was different from that reported above, but lignite showed negative charge. The electronegativity of Cu^{2+} was greater than that of Zn^{2+} . Under the electrostatic effect, Cu^{2+} was more likely to form a tight layer on the surface of lignite than Zn^{2+} , and continuously entered the dense layer from the diffusion layer until the charge balance on the surface of lignite. Therefore, the affinity of lignite to Cu^{2+} was higher than that of Zn^{2+} . So that the adsorption effect of lignite on copper ions was better than that of zinc.

From Fig. 2(d), 2(e) and Table 2, the isothermal adsorption line of lignite on Cu^{2+} was fitted, and the fitting effect of Langmuir model was better than that of Freundlich model. According to the Langmuir model fitting, the theoretical maximum adsorption capacity of lignite for Cu^{2+} was 228.59 mg/g. The isothermal adsorption line of Zn^{2+} adsorbed by lignite was used for fitting parameters, and the fitting effect of Freundlich model was better than that of Langmuir model. Lignite adsorption Zn^{2+} was a multi-molecular layer adsorption. Adsorption isotherm of Zn^{2+} on lignite Freundlich model fitting parameters $1/n$ was in the range of 0.5 ~ 1, indicating that the adsorption of Zn^{2+} by lignite was prone to occurrence. The value of K_F reflects the adsorption capacity of adsorbent. The larger the K_F value was, the better the adsorption performance of adsorbent was. The K_F value of Freundlich model of Cu^{2+} adsorption by lignite in binary metal system was higher than that of Freundlich model of Cu^{2+} adsorption by lignite in single Cu^{2+} system. Therefore, the adsorption performance of lignite on Cu^{2+} was better than that on Zn^{2+} in the binary system. Cu^{2+} was more competitive when lignite adsorbed Cu^{2+} and Zn^{2+} simultaneously.

From Fig. 2(f), after lignite adsorbing Cu^{2+} and Zn^{2+} , the pH of the system improved significantly. The pH improvement effect of lignite after Zn^{2+} adsorption was better than that of lignite after Cu^{2+} adsorption. The surface of lignite was charged negatively. In the process of adsorption of Cu^{2+} and Zn^{2+} , H^+ competes for the active sites adsorbed on the surface of lignite [37], resulting in a gradual increase in the pH of the system. At the same initial concentration, the equilibrium adsorption amount of Cu^{2+} by lignite was much higher than that of Zn^{2+} by lignite, indicating that Cu^{2+} was more easily adsorbed on the active sites on the surface of lignite than Zn^{2+} . Therefore, the pH improvement effect of Zn^{2+} system was more obvious than that of lignite adsorption Cu^{2+} . From Fig. 2(g), Ca^{2+} were dissolved in lignite when Cu^{2+} and Zn^{2+} were adsorbed. At the same concentration, the calcium concentration after adsorbing copper was higher than that after adsorbing zinc. It showed that Cu^{2+} was easier to ion exchange with Ca^{2+} in lignite than Zn^{2+} . After lignite adsorbing Cu^{2+} and Zn^{2+} , the turbidity of the system was below 50 NTU. After lignite adsorbing

Cu^{2+} and Zn^{2+} , it could precipitate completely after standing for 2.5 h. As adsorbent lignite is easy to recover, and not easy to produce secondary pollution.

3.3. Leaching of Pollutants from Lignite after Adsorption of Cu^{2+} and Zn^{2+}

Fig. 2(h) showed that the concentrations of copper and zinc ions in lignite leaching solution were 0.0007 mg/L and 0.0009 mg/L, respectively. The concentrations of copper and zinc ions in lignite leaching solution after adsorbing copper were 0.0460 mg/L and 0.0010 mg/L, respectively. The concentrations of copper and zinc ions in lignite leaching solution after adsorbing zinc were 0.0004 mg/L and 0.0460 mg/L, respectively. The concentrations of copper and zinc ions in lignite leaching solution after adsorbing copper and zinc were 0.0066 mg/L and 0.0420 mg/L, respectively. The leaching concentration of Cu^{2+} met the China National Surface Water Quality Standard (GB/T14848-9) type II water, and Zn^{2+} met the type I water. So lignite after adsorption of copper and zinc does not release secondary pollution.

3.4. Adsorption Mechanism

3.4.1. FT-IR analysis and EDS analysis

From Fig. 3(a), after the adsorption of Cu^{2+} , the OH stretching vibration absorption peak of lignite at $3,400\text{ cm}^{-1}$ corresponding to the adsorption of free water increased. The reason is that the carboxyl and hydroxyl functional groups on the surface of lignite molecule provided multiple adsorption sites for water molecules. Water molecules were easily adsorbed on the surface of lignite molecule through hydrogen bonding, resulting in the enhancement of OH stretching vibration absorption peak of lignite adsorbed free water in infrared spectrum. After adsorption of Cu^{2+} , the OH signal in the aromatic structure of lignite at $3,050$, $1,600$ and $1,450\text{ cm}^{-1}$ weakened, and the free water signal enhanced, indicating that a certain amount of hydroxyl water released and the crystal structure collapsed. This is mainly due to the coordination between oxygen atoms in aromatic structure and Cu^{2+} , resulting in the removal of hydroxyl water. After adsorption of Cu^{2+} , the change of lignite in the range of $650\sim 900\text{ cm}^{-1}$ corresponded to the series of absorption peaks of complex C-H out-of-plane bending vibration, indicating that the crystal structure of lignite underwent a certain collapse. From Fig. 3(b), after Zn^{2+} adsorption, the OH stretching vibration signal in the corresponding structure of lignite enhanced near $3,692$ and $3,620\text{ cm}^{-1}$. An isolated electron pair of oxygen atoms existed in the oxygen-containing functional group of lignite, which has strong electrophilicity and is easy to form hydrogen bonds with water molecules [38], resulting in the enhancement of OH stretching vibration signal in the lignite structure. The C-O stretching vibration peaks of ethers, alcohols and phenols near $1,200$ and $1,050\text{ cm}^{-1}$ enhanced after Zn^{2+} adsorption, indicating that Zn^{2+} coordinated with oxygen atoms in lignite molecular structure. The change of C-H signal of lignite after Zn^{2+} adsorption was not obvious, and the crystal structure of surface lignite did not change greatly. From Fig. 3(c), the changes of lignite after adsorption of Cu^{2+} and Zn^{2+} were similar to those of lignite after adsorption of Cu^{2+} . The OH stretching vibration absorption peak corresponding to the adsorption of free water enhanced at $3,400\text{ cm}^{-1}$. The OH signal in the

aromatic structure weakened at 3050, 1600 and 1450 cm^{-1} , and the free water signal enhanced. This phenomenon indicated that the oxygen atoms in the aromatic structure coordinated with Cu^{2+} and Zn^{2+} , and there was removal of a certain amount of hydroxyl water. In the meantime, the carboxyl and hydroxyl functional groups on the surface of lignite molecule were adsorbed on the surface of lignite molecule through hydrogen bonding, resulting in the enhancement of OH stretching vibration absorption peak of lignite

adsorbing free water in infrared spectrum. In the range of 650~900 cm^{-1} , a series of absorption peaks corresponding to the complex C-H out-of-plane bending vibration changed, the crystal structure underwent certain collapse. But the overall change was not as obvious as lignite after Cu^{2+} adsorption.

EDS was used to detect lignite, lignite after adsorption of Cu^{2+} , lignite after adsorption of Zn^{2+} and lignite after adsorption of Cu^{2+} and Zn^{2+} , the results are shown in Fig. 3(d)~(g). It can be seen

Fig. 3. FT-IR spectra and EDS results before and after lignite adsorption (a) FT-IR spectra of lignite adsorbing Cu^{2+} (b) FT-IR spectra of lignite adsorbing Zn^{2+} (c) FT-IR spectra of lignite adsorbing Cu^{2+} and Zn^{2+} (d) EDS image of raw lignite (e) EDS image of lignite adsorbing Cu^{2+} (f) EDS image of lignite adsorbing Zn^{2+} (g) EDS image of lignite adsorbing Cu^{2+} and Zn^{2+} .

from EDS that lignite mainly contained C, O, Al, Si, Au, S and Ca. Their contents were 64.02%, 12.82%, 2.66%, 8.50%, 5.70%, 4.36% and 0.25%, respectively. After adsorption of Cu^{2+} , 1.09% of Cu element appeared in lignite, 0.99% of Zn element appeared in lignite after adsorption of Zn^{2+} , 0.90% of Cu element and 0.80% of Zn element appeared in lignite after adsorption of Cu and Zn. EDS results show that lignite can adsorb Cu^{2+} and Zn^{2+} on the surface of lignite, resulting in the occurrence of Cu and Zn elements on the surface of lignite, and the adsorption amount of Cu^{2+} on lignite was greater than that of Zn^{2+} . The results are consistent with the adsorption test results.

3.4.2. XPS analysis

From Fig. 4(a)~(d), there were mainly C, O, Ca, Fe, N, S and Si elements in raw lignite. Cu2p3 peak appeared in lignite after adsorption of Cu^{2+} . Zn2p peak appeared in lignite after adsorption of Zn^{2+} . Cu2p3 peak and Zn2p peak appeared in lignite after adsorption of Cu^{2+} and Zn^{2+} . It indicates that chemical adsorption existed in the adsorption of Cu^{2+} and Zn^{2+} by lignite. From Table 3, the content of Ca in lignite after adsorption of Cu^{2+} , lignite after adsorption of Zn^{2+} and lignite after adsorption of Cu^{2+} and Zn^{2+} had different degrees of reduction, indicating that Ca^{2+} in lignite had ion exchange with Cu^{2+} and Zn^{2+} in the process of lignite adsorption of Cu^{2+} or Zn^{2+} . The content of O in lignite after Cu^{2+} adsorption, Zn^{2+} adsorption, and Cu^{2+} and Zn^{2+} adsorption increased to varying degrees, indicating that the carboxyl and hydroxyl functional groups on the surface of lignite molecules were adsorbed on the surface of lignite molecules by hydrogen bonds with water molecules, in the process of lignite adsorbing Cu^{2+} or Zn^{2+} . The content of S in lignite after adsorption of Cu^{2+} , adsorption of Zn^{2+} and adsorption of Cu^{2+} and Zn^{2+} increased in varying degrees, indicating

that SO_4^{2-} could react with some functional groups in lignite to adsorb on the surface of lignite.

In Fig. 4(e)~(h), the peak areas of $\text{C1s}(\text{CO}_3^{2-})$ of lignite after adsorption of Cu^{2+} , adsorption of Zn^{2+} and adsorption of Cu^{2+} and Zn^{2+} reduced compared with those of original lignite. The relative contents of $\text{C1s}(\text{CO}_3^{2-})$ of lignite after adsorption of Cu^{2+} , adsorption of Zn^{2+} and adsorption of Cu^{2+} and Zn^{2+} in Table 3 correspondingly reduced, indicating that CO_3^{2-} generated CuCO_3 and ZnCO_3 precipitated with Cu^{2+} and Zn^{2+} in the process of lignite adsorbing Cu^{2+} and Zn^{2+} . The relative content of C1sC-C in lignite after adsorption of Cu^{2+} , Zn^{2+} and adsorption of Cu^{2+} and Zn^{2+} decreased compared with raw lignite, and the relative content of C1sC-C in lignite after adsorption of Cu^{2+} and adsorption of Cu^{2+} and Zn^{2+} had same variable quantity, indicating that the structure of lignite changed in the process of adsorption of Cu^{2+} or Zn^{2+} . The structure of lignite changed obviously after adsorption of Cu^{2+} , which was consistent with the results of FT-IR analysis. The relative content of C1sC-O in lignite after adsorption of Cu^{2+} , adsorption of Zn^{2+} and adsorption of Cu^{2+} and Zn^{2+} increased compared with the original lignite, indicating that oxygen atoms in lignite structure coordinated with Cu^{2+} and Zn^{2+} in the process of lignite adsorption. Thus the relative content of C1sC-O in lignite increased with removal of hydroxyl water.

Fig. 5(a)~(d) shows that the peak areas of Ca2p3CaCO_3 of lignite after adsorption of Cu^{2+} , adsorption of Zn^{2+} and adsorption of Cu^{2+} and Zn^{2+} were smaller than that of raw lignite. The change of Ca2p3CaCO_3 peak of lignite after adsorption of Cu^{2+} was the same as that of lignite after adsorption of Cu^{2+} and Zn^{2+} . It indicates that Cu^{2+} or Zn^{2+} exchanged ion with Ca^{2+} to generate CuCO_3 or ZnCO_3 in the process of adsorption of Cu^{2+} or Zn^{2+} by lignite

Table 3. Changes of Relative Content of Elements in Lignite Before and After Adsorption

	Atomic/%			
	Raw lignite	Lignite after Cu^{2+} adsorption	Lignite after Zn^{2+} adsorption	Lignite after adsorption of Cu^{2+} and Zn^{2+}
C1s	66.89	51.3	50.71	55.41
Ca2p	2.03	0.59	1.11	1.06
Cu2p	0	5.39	0	4.23
Fe2p	1.09	3.02	1.66	2.59
N1s	2.42	1.97	1.54	1.8
O1s	24.55	32.83	34.42	30.33
S2p	0.74	2.93	1.85	2
Si2p	2.27	1.97	2.92	2.21
Zn2p	0	0	5.79	0.37
$\text{C1s}(\text{CO}_3^{2-})$	7.55	6.98	6.61	6.53
C1sC-C	82.38	70.85	74.85	75.32
C1sC-O	7.35	8.66	7.75	8.43
Cu2p3 CuO	0	0.78	0	0.71
$\text{Cu2p3 CuSO}_4/\text{CuCO}_3$	0	3.4	0	2.66
$\text{Cu2p3 satellite peak1}$	0	3.98	0	1.48
$\text{Cu2p3 satellite peak2}$	0	4.33	0	2.98
Zn2p3 ZnO	0	0	6.26	0.55
$\text{Zn2p3 ZnSO}_4/\text{ZnCO}_3$	0	0	3.32	0

Fig. 4. XPS full-spectrum scanning map before and after lignite adsorption and XPS map of lignite C1s (a) XPS full-spectrum scanning diagram of raw lignite (b) XPS full-spectrum scanning diagram of lignite after adsorption of Cu^{2+} (c) XPS full-spectrum scanning diagram of lignite after Zn^{2+} adsorption (d) XPS full-spectrum scanning diagram of lignite after Cu^{2+} and Zn^{2+} adsorption (e) XPS spectra of raw lignite (f) XPS spectra of lignite C1s (g) XPS spectra of lignite C1s after Zn^{2+} adsorption (h) XPS spectra of lignite C1s after Cu^{2+} and Zn^{2+} adsorption.

in single metal system. Thus Cu^{2+} or Zn^{2+} was adsorbed on the surface of lignite. In the process of lignite adsorbing Cu^{2+} and Zn^{2+} in binary metal system, only Cu^{2+} and Ca^{2+} ion exchange occurred, and CuCO_3 was generated. Zn^{2+} did not participate in ion exchange.

Table 3 shows the relative content changes of chemical states of Cu and Zn in lignite before and after adsorption. Fig. 5(e) and Fig. 5(g) show that Cu^{2+} was adsorbed on lignite surface in Cu^{2+} , CuO and CuCO_3 chemical states after adsorption, and Zn^{2+} was adsorbed on lignite surface in ZnO and ZnCO_3 chemical states after adsorption. In the single metal system, the adsorption of Cu^{2+} by lignite involved electrostatic, coordination and ion exchange, and the adsorption process was mainly physical adsorption. The adsorption process of Zn^{2+} by lignite involved electrostatic, coordination and ion exchange, and the adsorption process was mainly

chemical adsorption. From Fig. 5(e) and Fig. 5(f), Cu^{2+} was adsorbed on the surface of lignite in the chemical states of Cu^{2+} , CuO and CuCO_3 in the single metal system and binary metal system after adsorption, indicating that the mechanism of Cu^{2+} adsorption by lignite in the binary metal system was the same as that on lignite in the single metal system, with both chemical and physical adsorption. From Fig. 5(g) and Fig. 5(h), Zn^{2+} was adsorbed on the surface of lignite in the chemical state of ZnO and ZnCO_3 after adsorption in the single metal system. In the binary metal system, Zn^{2+} was adsorbed on the surface of lignite by ZnO chemical state after adsorption, indicating that the adsorption process of Zn^{2+} on lignite in single metal system involved electrostatic, coordination and ion exchange. However in the binary metal system, Zn^{2+} was adsorbed on the surface of lignite only through coordination. It can be seen that lignite had selectivity on Cu^{2+}

Fig. 5. XPS spectra of Ca2p, Cu2p and Zn2p in lignite (a) Ca2p map of raw lignite (b) Ca2p map of lignite after Cu^{2+} adsorption (c) Ca2p map of lignite after Zn^{2+} adsorption (d) Ca2p map of lignite after Cu^{2+} and Zn^{2+} adsorption (e) Cu2p map of lignite after adsorption of Cu^{2+} (f) Cu2p map of lignite after adsorption of Cu^{2+} and Zn^{2+} (g) Zn2p map of lignite after Zn^{2+} adsorption (h) Zn2p map of lignite after Cu^{2+} and Zn^{2+} adsorption.

in the binary metal system, and the adsorption performance of Cu^{2+} was better than that of Zn^{2+} .

4. Conclusions

- (1) The adsorption kinetics of Cu^{2+} and Zn^{2+} fitted the pseudo-first-order kinetic model, and the equilibrium adsorption capacities of Cu^{2+} and Zn^{2+} were 67.84 mg/g and 55.5 mg/g, respectively. The adsorption of Cu^{2+} by lignite was more in line with Langmuir model. The adsorption of Zn^{2+} on lignite fitted Freundlich model better.
- (2) Copper and zinc removal from lignite mainly depended on physical adsorption, coordination and ion exchange. There was competitive adsorption between Cu^{2+} and Zn^{2+} , and lignite had better adsorption effect on copper. The adsorbed copper ions

were mainly adsorbed on the surface of lignite in the chemical states of Cu^{2+} , CuO and CuCO_3 , and Zn^{2+} was adsorbed on the surface of lignite in the chemical states of ZnO and ZnCO_3 .

- (3) The leaching experiments show that the concentration of Cu^{2+} were 0.0007 mg/L, 0.0460 mg/L, 0.0004 mg/L and 0.0066 mg/L, the concentration of Zn^{2+} were 0.0009 mg/L, 0.0010 mg/L, 0.0460 mg/L and 0.0420 mg/L. The release concentration of lignite pollutants adsorbed copper and zinc meets the national water quality standard of China (GB/T 14848-9).

Acknowledgments

This work was supported by the National Natural Science Foundation of China under Grant (41672247), Liaoning Province's "Program for Promoting Liaoning Talents" under Grant

(XLYC1807159), discipline innovation team of Liaoning Technical University under Grant (LNTU20TD-21).

Author Contributions

J.D. (Professor) made the experiment plan and guided the experiment in the whole process. S.B. (Ph.D. student) was in charge of data analysis and paper writing. J.Y. (Senior Engineer) and D.W. (Professor) was in charge of experiment guidance and paper revision. J.S. (Master student) and Y.D. (Ph.D. student) was responsible for detection.

References

- Feng Q, Li T, Qian B, et al. Chemical Characteristics and Utilization of Coal Mine Drainage in China. *Mine Water Environ.* 2014;33:276-286.
- Gao J, Xu L, Wang Y, et al. Treatment of Acid Wastewater Containing Uranium by Sulfate Reducing Bacteria. In: Merkel B., Arab A, eds. Uranium - Past and Future Challenges. Springer, Cham; 2015. p. 377-386.
- Wright IA, McCarthy B, Belmer N, et al. Subsidence from an Underground Coal Mine and Mine Wastewater Discharge Causing Water Pollution and Degradation of Aquatic Ecosystems. *Water Air Soil Pollut.* 2015;226:348.
- Aisling D. O'Sullivan, Murray DA, Otte ML. Removal of Sulfate, Zinc, and Lead from Alkaline Mine Wastewater Using Pilot-scale Surface-Flow Wetlands at Tara Mines, Ireland. *Mine Water Environ.* 2004;23:58-65.
- Saria L, Shimaoka T, Miyawaki K. Leaching of heavy metals in acid mine drainage. *Waste Manag Res.* 2006;24:134-140.
- Sasowsky ID, Foos A, Miller CM. Lithic controls on the removal of iron and remediation of acidic mine drainage. *Water Res.* 2000;34:2742-2746.
- Kuang JL, Huang LN, Chen LX, et al. Contemporary environmental variation determines microbial diversity patterns in acid mine drainage. *ISME J.* 2013;7:1038-1050.
- Johnson DB, Hallberg KB. Acid mine drainage remediation options: a review. *Sci. Total Environ.* 2005;338:3-14.
- Anawar HM. Sustainable rehabilitation of mining waste and acid mine drainage using geochemistry, mine type, mineralogy, texture, ore extraction and climate knowledge. *J. Environ. Manage.* 2015;158:111-121.
- Wang X, Cao XQ, Li L, et al. Research Progress of Treatment of Acid Mine Drainage by Low-cost Adsorbents. *Metal Mine* 2018;7:7-12.
- Papirio S, Villa-Gomez DK, Esposito G, et al. Acid Mine Drainage Treatment in Fluidized-Bed Bioreactors by Sulfate-Reducing Bacteria: A Critical Review. *Crit. Rev. Environ. Sci. Technol.* 2013;43:2545-2580.
- Wei TT, Yu Y, Hu ZQ, et al. Research Progress of Acid Mine Drainage Treatment Technology in China. *Appl. Mech. Mater.* 2013;409-410:214-220.
- Senko JM, Zhang G, McDonough JT, et al. Metal Reduction at Low pH by a Desulfosporosinus species: Implications for the Biological Treatment of Acidic Mine Drainage. *Geomicrobiol. J.* 2009;26:71-82.
- Nevatalo L. Bioreactor Applications Utilizing Mesophilic Sulfate-Reducing Bacteria for Treatment of Mine Wastewaters at 9-35°C [dissertation]. Tampere: Tampere University of Technology; 2010.
- Liao J, Fei Y, Marshall M, et al. Hydrothermal dewatering of a Chinese lignite and properties of the solid products. *Fuel* 2016;180:473-480.
- Dong LH, Yuan Q, Yuan HL. Changes of chemical properties of humic acids from crude and fungal transformed lignite. *Fuel* 2006;85:2402-2407.
- Huang B, Liu G, Wang P, et al. Effect of Nitric Acid Modification on Characteristics and Adsorption Properties of Lignite. *Processes* 2019;7:167-183.
- He Q, Wang G, Chen Z, et al. Adsorption of anionic azo dyes using lignite coke by one-step short-time pyrolysis. *Fuel* 2020;267:117140.
- Thapa KB, Qi Y, Hoadley AFA. Interaction of polyelectrolyte with digested sewage sludge and lignite in sludge dewatering. *Colloid. Surface. A.* 2009;334:66-73.
- Tu Y, Feng P, Ren Y, et al. Adsorption of ammonia nitrogen on lignite and its influence on coal water slurry preparation. *Fuel* 2019;238:34-43.
- Polat H, Molva M, Polat M. Capacity and mechanism of phenol adsorption on lignite. *Int. J. Miner. Process.* 2006;79:264-273.
- Uçurum M. A study of removal of Pb heavy metal ions from aqueous solution using lignite and a new cheap adsorbent (lignite washing plant tailings). *Fuel* 2009;88:1460-1465.
- He Q, Ruan P, Miao Z, et al. Adsorption of direct yellow brown D3G from aqueous solution using loaded modified low-cost lignite: Performance and mechanism. *Environ. Technol.* 2019;1-10.
- He Q, Cui R, Miao Z, et al. Improved removal of Congo Red from wastewater by low-rank coal using micro and nanobubbles. *Fuel* 2021;291:120090.
- Dinesh M, Subhash C. Removal and recovery of metal ions from acid mine drainage using lignite—A low cost sorbent. *J. Hazard. Mater.* 2006;137:1545-1553.
- Fethiye G, Erol P. Adsorption of Cr(III) ions by Turkish brown coals. *Fuel Process Technol.* 2005;86:875-884.
- Reed BE, Matsumoto MR. Modeling Cadmium Adsorption by Activated Carbon Using the Langmuir and Freundlich Isotherm Expressions. *Sep. Sci. Technol.* 1993;28:2179-2195.
- Covelo EF, Andrade ML, Vega FA. Heavy metal adsorption by humic umbrilsols: selectivity sequences and competitive sorption kinetics. *J. Colloid. Interf. Sci.* 2004;280:1-8.
- Zhang RH, Wang B, Ma HZ. Studies on Chromium (VI) adsorption on sulfonated lignite. *Desalination* 2010;255:61-66.
- Shrestha S, Son G, Lee SH, et al. Isotherm and thermodynamic studies of Zn (II) adsorption on lignite and coconut shell-based activated carbon fiber. *Chemosphere* 2013;92:1053-1061.
- Dada AO, Olalekan AP, Olatunya AM, et al. Langmuir, Freundlich, Temkin and Dubinin-Radushkevich Isotherms Studies of Equilibrium Sorption of Zn²⁺ Unto Phosphoric Acid Modified Rice Husk. *Russ J. Appl. Chem.* 2012;3:38-45.
- Wang J, Guo X. Adsorption isotherm models: Classification,

- physical meaning, application and solving method. *Chemosphere* 2020;258:127279.
33. Sun JT, Li MF, Zhang ZH, et al. Unravelling the adsorption disparity mechanism of heavy-metal ions on the bio-mass-derived hierarchically porous carbon. *Appl. Surf. Sci.* 2019;471:615-620.
 34. Wang LJ, Liu XL, Weng ML, et al. Study on the Effect of Amphoteric Bagasse Hemicellulose on Heavy Metal Adsorption. *Adv. Mater. Res.* 2011;399-401:1282-1288.
 35. Mahamadi C, Nharingo T. Competitive adsorption of Pb^{2+} , Cd^{2+} and Zn^{2+} ions onto Eichhornia crassipes in binary and ternary systems. *Bioresour. Technol.* 2010;101:859-864.
 36. Oh S, Kim DS. Adsorption features of heavy metal ions on activated carbon in single and multisolute systems. *J. Environ. Sci. Heal. A* 2014;49:710-719.
 37. Samra SE. Removal of Ni^{2+} and Cu^{2+} Ions from Aqueous Solution on to Lignite-based Carbons. *Adsorpt. Sci. Technol.* 2000;18: 761-775.
 38. Wang GL, Zhou LS, Zhao Y, et al. Mechanism of water polymer adsorption on lignite molecule. *Coal Eng.* 2018;50:136-140.