Modelling CO₂ and NO_x on signalized roundabout using modified adaptive neural fuzzy inference system model

Ghassan Sulaiman¹, Mohammad K. Younes^{2†}, Ghassan A. Al-Dulaimi²

¹Department of Civil Engineering, Aqaba University of Technology, 11947, Aqaba, Jordan

²Department of Civil Engineering, Philadelphia University, 19392, Amman, Jordan

ABSTRACT

Air quality and pollution have recently become a major concern; vehicle emissions significantly pollute the air, especially in large and crowded cities. There are various factors that affect vehicle emissions; this research aims to find the most influential factors affecting CO₂ and NO_x emissions using Adaptive Neural Fuzzy Inference System (ANFIS) as well as a systematic approach. The modified ANFIS (MANFIS) was developed to enhance modelling and Root Mean Square Error was used to evaluate the model performance. The results show that percentages of CO₂ from trucks represent the best input combination to model. While for NO_x modelling, the best pair combination is the vehicle delay and percentage of heavy trucks. However, the final MANFIS structure involves two inputs, three membership functions and nine rules. For CO₂ modelling the triangular membership function is the best, while for NO_x the membership function is two-sided Gaussian.

Keywords: Air pollution, Air quality index, ANFIS, Traffic congestion, Transportation emissions

1. Introduction

The growth in urban traffic congestion has become a serious problem in all large metropolitan areas; it significantly affects the economy and travel behaviour. In addition, it is a cause of discomfort for millions of motorists [1, 2], and has harmful impacts on human health and metropolitan air quality [3]. For instance, in the US, congestion is responsible for wasting 101 billion USD annually. This figure accounts for an extra 2 billion gallons of fuel and 4.8 billion hours of wasted time [4]. Traffic congestion involves major contributing factors such as human, vehicle, and traffic composition [5]. Traffic composition is the distribution of vehicle type; this includes passenger car, mini bus and/or heavy vehicles.

Congestion causes chronic environmental problems such as air and noise pollution. Researchers have recently developed various models to estimate air pollutants resulting from transportation sectors. For instance, multivariate linear regression was implemented to link traffic density and the presence of diesel vehicles emitting air pollutants [6]. Real time information on traffic density, diesel vehicles, and traffic voice (noise) was used to model indoor and outdoor air pollutants [7]. In addition, Adaptive Neural Fuzzy

Inference System (ANFIS) was implemented to predict the traffic flow over a short period using 104 changeable parameters [8]. ANFIS has been implemented to determine the level of safety on roads in relation with traffic density, speed and road plane visibility [9]. The results have shown ANFIS ability to enhance safety levels on roads; ANFIS was used to improve the work of Traffic Controllers in decreasing traffic congestion.

The performance of ANFIS controllers in terms of delay, average waiting time and queue length, was analysed and compared with the performances of traditional controllers and normal fuzzy controllers [10]. The results showed that ANFIS performance was superior. ANFIS has become popular for modelling environmental systems due to its accuracy, efficiency and capacity to handle large amount of stochastic (linear, nonlinear) data. For example, ANFIS was used to model driver behaviour using their reaction time and delay [11]. Furthermore, to help developing countries properly estimate solar radiation and benefit from it, ANFIS was implemented to model solar radiation based on metrological variables [12].

Despite its advantages, the complexity of ANFIS model topology, especially at a large number of input variables, is considered the main limitation of its wide implementation. This is because

This is an Open Access article distributed under the terms of the Creative Commons Attribution Non-Commercial License (<http://creativecommons.org/licenses/by-nc/3.0/>) which permits unrestricted non-commercial use, distribution, and reproduction in any medium, provided the original work is properly cited.

Copyright © 2018 Korean Society of Environmental Engineers

Received July 19, 2017 Accepted October 10, 2017

[†] Corresponding author

Email: myounes@philadelphia.edu.jo

Tel: +962-64799000 Fax: +962-64799040

ORCID: 0000-0001-5548-4821

ANFIS generates and tries all possible combinations of premises, which are a function of the number of variables. For instance, if a system has (n) inputs and (P) premises, then the number of available rules equals ($N = P^n$). Thus, ANFIS implementation may not be feasible for several variable reasons. Furthermore, human expertise is necessary to optimize the ANFIS structure; however, this solution is not always viable. For instance, if five inputs and three membership are used in a system, then the rule number becomes ($3^5 = 243$ rules), which significantly increases the total number of parameters and computing time [13]. However, a modified ANFIS (MANFIS) is recommended to overcome this limitation.

This study aims to propose a model to estimate CO_2 and NO_x at the signalized roundabouts. It links the traffic conditions, including delays and percentages of heavy trucks, with the vehicle emissions to estimate air pollution. It applies a systematic search algorithm to choose the best available representative input variables. After that, it modifies the model to minimize the modelling complexity and error as well as providing effective tools to simulate such environmental applications. Such approach could assist decision makers in properly establishing sustainable traffic plans to reduce the impact of traffic congestion on air quality.

2. Methodology

2.1. Study Area and Data Collection

Corum city is the centre of the Corum governorate that is located at the north of Turkey. To analyse the traffic situation in the city, the main intersections were categorized into signalized and non-signalized intersections. This study analysed signalized roundabouts resulting in a total of eight intersections during the summer of 2015. Cameras were also placed on each intersection (numbers according to the size of the intersection) with the aim of defining traffic volume at rush hours. Rush hour periods were divided into three periods, these included mornings, (7:30-9:30) to cover business time in Turkey that starts at 9:00 AM. The second period was between 12:00-14:00 (end of schools), and the third period was between 16:30-18:30 (end of business day). Thus, for each of these intersections six hours of traffic video were recorded.

The recorded data for each intersection yielded vehicle counts and speeds of 6-types of vehicles: automobile, taxi, minibus, van, bus and heavy trucks. The analysis time of the recorded data was 54 h. Fig. 1 shows the 6th signalized roundabout as a satellite photo. It shows the location of the leg recorder. Table 1 shows a sample of traffic recorded data along the morning rush hours (7:30-9:30). Moreover, it represents an example of how data was extracted. For instance, 1-4 represent the total number of each vehicle type that is leaving leg one into leg number four. Furthermore, the total column at the table represents the total number of vehicles that are leaving from each leg at the roundabout to other legs. Air quality was also monitored during the same period, in a single site at each intersection that is located downwind [14], using Genesis portable air monitoring made by Thermo Fisher at around 15-30 m from the intersection. The measurement was

taken every fifteen minutes then the hourly average was used to represent the concentration at peak hour. Finally, modelling and data analysis were performed using MATLAB (7.14).

Fig. 1. Abide signalized roundabout satellite photo (6th roundabout).

2.2. Selection of Optimum Inputs and MANFIS Model Development

In order to minimize the data input and simplify the model structure, input selection was implemented. Initially, five inputs were used against each output; these were NO_x and CO_2 , respectively. The inputs represent vehicle average speed, traffic delay per second, percentage of mini trucks (%MT) (2.5 PCU), heavy truck percentage (%HT), and the total of heavy and mini trucks (%H&M). The optimum pair combination (input-output pair) was then determined by searching for the combination with lowest Root Mean Square Error (RMSE). The selection of optimum input number was based on a single iteration using the general bell shape fuzzy function and two membership functions by using a hybrid of least-squares and back-propagation gradient descent methods. In addition, the model performance was evaluated using the following statistical equation [15, 16].

$$RMSE = \sqrt{\sum_{t=1}^n \frac{(x_t - x_0)^2}{n}} \quad (1)$$

Where X_t is the actual output and X_0 is the predicted output, n is the number of the outputs.

ANFIS is a multilayer feed-forward network; it performs a fuzzy logic function on incoming signals. To build the fuzzy logic structure, it is essential to (i) select the model inputs (ii) determine the membership functions, and (iii) generate the fuzzy rules. Meanwhile, minimizing the model error needs an optimizing epoch's number, membership type and number. During the training phase, the shape of the membership function was modified in order to define the relation between input and output. This stage was repeated on several occasions (epochs) until the desired convergence was acquired (usually until the specified minimum square error between the ANFIS output and the actual one is achieved). However, for a first-order Sugeno fuzzy model, a common set of two fuzzy rules and a set of if-then rules are described as follows:

$$\text{Rule 1: If } x \text{ is } A_1 \text{ and } y \text{ is } B_1 \text{ THEN } f_1 = p_1x + q_1y + r_1 \quad (2)$$

$$\text{Rule 2: If } x \text{ is } A_2 \text{ and } y \text{ is } B_2 \text{ THEN } f_2 = p_2x + q_2y + r_2 \quad (3)$$

Table 1. Abide Signalized Roundabout Traffic Volume for Leg1

Recording time			Automobile			Minibus			Taxi			Public buses			Heavy trucks			Subtotal			Total
			1-2	1-3	1-4	1-2	1-3	1-4	1-2	1-3	1-4	1-2	1-3	1-4	1-2	1-3	1-4	1-2	1-3	1-4	
Morning period	7:30	7:45	36	14	34	8	2	7	3	0	2	1	0	2	1	1	1	49	17	46	112
	7:45	8:00	52	24	34	8	4	8	0	0	0	2	0	2	2	0	4	64	28	48	140
	8:00	8:15	65	16	36	7	4	7	4	1	4	1	0	2	5	0	1	82	21	50	153
	8:15	8:30	48	22	40	5	5	5	0	0	3	2	0	5	2	0	1	57	27	54	138
	8:30	8:45	61	14	27	9	2	4	0	0	2	5	0	3	0	0	0	75	16	36	127
	8:45	9:00	63	14	36	12	2	6	3	0	2	4	0	3	6	0	2	88	16	49	153
	9:00	9:15	58	21	30	10	7	5	2	1	1	1	0	3	2	1	2	73	30	41	144
	9:15	9:30	40	20	40	6	6	4	2	0	0	1	1	3	0	1	0	49	28	47	124

where A_i or B_j is a linguistic label (grade), such as “low” or “less”, and p_1, q_1, p_2, q_2 are the design parameters that are determined by the system developer [17]. Fig. 2 presents the ANFIS model structures, where the circular nodes are fixed and the square nodes have parameters to be learned. The shown five layers are characterized by training and testing phases. The model developer has the capability to choose among the available membership function types in accordance with system demand, simplicity, speed and convenience. The membership function is a parameterized function in which any changes in the corresponding parameters produce a change in the function shape. However, the selection of membership function should fall between 0 and 1 [18].

In this study, to develop MANFIS structure, several steps were implemented. First, optimizing the number of inputs and then determining the best input-output combinations by searching for the lowest error RMSE for training and checking. After that, altering the type of membership functions to determine the best one. Finally, determining the number of membership functions that reduce the RMSE [19, 20].

Fig. 2. ANFIS architecture Sugeno system.

3. Results and Discussion

3.1. Inputs Selection for CO₂ Modelling

The collected input variables were divided into training (the odd readings) and testing (the even readings). The available variables that may affect vehicles (gasoline and diesel) emissions were selected. It was imperative to choose the factors (inputs) that are relevant to the simulated system. The summary of the optimum twelve inputs and their combinations are shown in Fig. 3. To

Fig. 3. Summary of optimum input combinations for CO₂ modelling.

obtain these results, twenty-five combinations were tested. These combinations were single input-output, double input-output and tribal inputs-output. For levels of single input, the total heavy and mini trucks, and car speed, represent the best results with training RMSE are equal to 494 and 731 and checking RMSE are equal to 1,357 and 1,214, respectively.

For double inputs, the best combination is between the percentage of heavy trucks and average vehicle speed, its training RMSE equalled 0.005 and checking RMSE equalled 1,300. However other double inputs combination has relatively similar results, which combination is between the percentage of heavy trucks and the percentage of mini trucks which has RMSE for training equals to 303 and RMSE for checking equals to 861. For three inputs and single output, the best combination is between the average car's speed, percentage of heavy trucks and percentage of mini trucks as $RMSE_{\text{training}} = 0.002$ and $RMSE_{\text{checking}} = 973$. However, using three variables as inputs for the model did not significantly enhance performance. Thus, the optimum number of inputs is assumed to be two, and the best combination is between the heavy truck percentage and vehicle speed.

3.2. Inputs Selection for NO_x Modelling

Fig. 4 shows a summary of the best input combinations for modelling NO_x by testing all twenty-five possible combinations for single, double and tribal inputs. For a single input and one output that is NO_x, the percentage of heavy truck represents the best input with $RMSE_{\text{training}} = 59.2$ and $RMSE_{\text{checking}} = 489.4$, respectively. While for the combination of two inputs, the optimum one is between the delay and percentage of heavy trucks, its results

Fig. 4. Summary of optimum input combinations for NO_x modelling, are $\text{RMSE}_{\text{training}} = 59.02$ and $\text{RMSE}_{\text{checking}} = 167.6$, respectively. However, for NO_x modelling the combination of two input variables is considered as the optimum combination, since increasing the input number does not enhance the process significantly as shown in Fig. 4.

3.3. Final Structure of MANFIS Model

The performance of two input-output combinations for CO_2 and NO_x modelling is shown in Table 2. For carbon dioxide, the best representing pair combination is number five that is between

the vehicle speed and the percentage of heavy trucks with $\text{RMSE}_{\text{training}}$ equals 0.06 and $\text{RMSE}_{\text{testing}}$ equals 1,300.7. However, the high testing error may be due to limited training readings which could have been avoided by increasing the number of readings. In addition, the first combination generates a smaller error for the training phase, but it is not considered due to its high testing phase error. On the other hand, for NO_x modelling, the traffic delay and the percentage of heavy trucks are considered as the optimum input pair. It produces 0.02 and 253.0 for $\text{RMSE}_{\text{training}}$ and $\text{RMSE}_{\text{testing}}$, respectively.

After selecting the best input combination for both CO_2 and NO_x the best membership functions were determined. This was done by choosing from eight types of membership functions as shown in Table 3. In this phase, the hybrid training algorithm has been used. Furthermore, three membership functions and three epochs were implemented during the search process. The results show that the triangular membership function best represents CO_2 emission with $\text{RMSE}_{\text{training}} = 0.05$ and $\text{RMSE}_{\text{testing}} = 1,034.2$. While for NO_x modelling the best membership function is two-sided Gaussian with 0.007 and 241.7 for $\text{RMSE}_{\text{training}}$ and $\text{RMSE}_{\text{testing}}$, respectively.

To accomplish the MANFIS structure, the optimum number

Table 2. Summary of Optimum Inputs Selection Using Two Input Variables for CO_2 and NO_x

No	CO_2			No	NO_x		
	Inputs	$\text{RMSE}_{\text{training}}$	$\text{RMSE}_{\text{testing}}$		Inputs	$\text{RMSE}_{\text{training}}$	$\text{RMSE}_{\text{testing}}$
1	Delay; Speed	0.03	3,594.8	1	Delay; Speed	0.02	699.4
2	Delay; % HT	1.48	5,889.0	2 ^b	Delay; % HT	0.02	253.0
3	Delay; % MT	0.22	5,918.4	3	Delay; % MT	0.44	1,151.5
4	Delay; (H&M)	2.30	10,964.4	4	Delay; (H&M)	0.50	2,133.3
5 ^a	Speed; % HT	0.06	1,300.7	5	Speed; % HT	0.29	1,145.8
6	Speed; % MT	0.48	8,932.7	6	Speed; % MT	0.09	1,738.0
7	Speed; % (H&M)	0.19	1,944.0	7	Speed; % (H&M)	0.04	378.2
8	% HT; % MT	304.3	861.6	8	% HT; % MT	59.05	167.6
9	% HT; (H&M)	303.3	1,784.4	9	% HT; (H&M)	59.0	347.2
10	% MT; (H&M)	303.4	572.0	10	% MT; (H&M)	59.1	111.3

^a best combination for CO_2 modelling, ^b best combination for NO_x modelling

Table 3. Summary of the Performance of Various Membership Functions for CO_2 and NO_x

Code	Function Description	CO_2		NO_x	
		$\text{RMSE}_{\text{train}}$	$\text{RMSE}_{\text{test}}$	$\text{RMSE}_{\text{train}}$	$\text{RMSE}_{\text{test}}$
Trimf	Triangular MF	0.05 ^a	1,034.2 ^a	0.013	315.1
trapmf	Trapezoidal MF	0.03	1,449.8	0.004	310.4
gbellmf	Generalized bell curve MF	0.05	1,139.2	0.18	339.7
gaussmf	Gaussian curve MF	0.2	1,106.9	0.007	279.0
gauss2mf	Two-sided Gaussian MF	0.04	1,393.4	0.007 ^b	241.7 ^b
pimf	Pi-shaped curve MF	0.03	1,392.0	0.004	310.5
dsigmf	Composed of the difference between two sigmoidal MF	0.04	1,321.6	0.005	309.4
psigmf	Product of two sigmoid MF	0.36	1,325.6	0.005	309.4

^a The best membership function performance for CO_2 , ^b The best performance of the membership function for NO_x

Fig. 5. Final MANFIS structures for CO₂ and NO_x models.

Table 4. Performance Summary of Various Membership Functions for CO₂ and NO_x

No of function	CO ₂		NO _x	
	RMSE _{train}	RMSE _{test}	RMSE _{train}	RMSE _{test}
2	355.1	967.8	67.1	322.7
3 ^a	0.05	1,034.2	0.007	241.7
4	0.04	1,460	0.006	403.1
5	0.05	1,365	0.07	416.7
6	0.04	1,731	0.08	421.9
7	2,068	2,578	0.07	423.1

^a The best function number

of membership function was determined by keeping the epoch number constant (3 epochs) and altering the number of membership functions from 2 to 7. However, the selected optimum input combinations for both CO₂ and NO_x were used in this search. The optimum number of membership function was selected based on the generated smallest RMSE for training and testing phases. Table 4 shows the performance of the model with different function numbers. The best performance for both CO₂ and NO_x was achieved with three functions. The training RMSE of CO₂ and NO_x were 0.05 and 0.007, respectively, while for the testing phase it was 1,034.2 and 241.7 for CO₂ and NO_x, respectively. However, as shown in Table 4 increasing the numbers of membership functions does not enhance the model performance.

Developing the model structure by applying MANFIS enhances the overall modelling performance. For instance, it reduces the training RMSE for CO₂ by 16% and for NO_x by 65%, respectively, while it reduces the testing RMSE for CO₂ by 71% and for NO_x by 4%, respectively. Finally, the final MANFIS structure shown in Fig. 5 illustrates structures of MANFIS model for both CO₂ and NO_x, respectively. It shows the two inputs, membership functions, the three membership functions, the nine fuzzy rules and the desired output.

Fig. 6. Surface viewer of % of heavy truck, speed and CO₂

Fig. 7. Surface viewer of % of heavy truck, delay and NO_x.

Fig. 6 shows the effect of the vehicles' speed and percentage of heavy truck on CO₂ emission. For instance, for a speed value of 10 km/h, as the percentage of heavy trucks decreases, CO₂ emission increases. This is related to the increase the number of lighter, or gasoline trucks which have more CO₂ emission than the heavy truck [6]. On the other hand, increasing the speed will reduce CO₂ emissions. This goes back to different densities of diesel and gasoline. Thus, the consumption varies, and diesel consumption is less than gasoline.

Fig. 7 shows the effects of delay and the heavy truck percentage on NO_x emission. The NO_x emission can be divided into two categories. The first being 20 s per vehicle; in this region, increasing the percentage of trucks will decrease the NO_x emissions. Otherwise, the second region is for delays of more than 20 s; in this region, increasing the percentage of heavy truck increased the NO_x emission. Moreover, the highest NO_x emission was at the largest delay (55 s) and highest heavy truck percentage. Increasing the heavy truck percentage reduced the traffic movement and increased the waiting time for all vehicles at the road; therefore, emissions increased. In addition, heavy trucks, usually diesel vehicles, comparatively emit higher NO_x than gasoline vehicles during times of being stationary. Therefore, its contribution is tangible for NO_x emission [21].

4. Conclusions

This study analyses negative implications of traffic congestion on air quality, especially under signalized roundabouts and possibly elsewhere. The developed model could assist municipal planning boards, traffic and environmental engineers to identify planning and management measures and policies for reducing air pollution as a result of traffic congestion in urban zones. The main objective of this research was to investigate the effect of traffic composition variables on CO_2 and NO_x density on signalized roundabouts, whilst maintaining an accepted degree of accuracy using MANFIS in order to reduce complexity and data collection time. The traffic composition variables included in this study were the percentage of minibuses, percentage of heavy trucks, average delay, and average speed. Proper input selection enhanced model performance. However, environmental systems have limitations to data records. These limitations are essentially related to accuracy, budget, time, and reliability of the data. Therefore, modelling environmental systems saves time, effort and cost whilst maximizing model usability.

The results indicate that vehicle speed and the percentage of heavy trucks are the main input variables to estimate the emission of CO_2 . Meanwhile, delays and percentage of heavy trucks are the main inputs for the NO_x modelling. However, there is some suggestion of potential conflicts with some aspects of current planning ideas; specific questions about the advisability of heavy truck entry permission to the city centre, especially during peak periods have arisen. These suggest that environmental and safety consequences of these concepts in specific places should be dealt with. Finally, it is recommended to replicate the investigation of the relation between traffic conditions and air pollutants elsewhere to see if similar findings are obtained to support the confidence in our conclusions.

Acknowledgments

The authors are grateful and thankful for the head of Corum City Council and all the people in the City Council for their help and support during data collection and analysis. Moreover, high appreciation is shown for Philadelphia University and Aqaba

University of Technology for funding the project.

References

1. Jin J, Rafferty P. Does congestion negatively affect income growth and employment growth? Empirical evidence from US metropolitan regions. *Transport Policy* 2017;55:1-8.
2. Suleiman GM, Bezgin NÖ, Ergun M, Gürsoy M, Karasahin M. Effects of speed management and roadway parameters on traffic flow along arterials. In: Proceedings of the Institution of Civil Engineers-Transport. Thomas Telford Ltd.; 2017.
3. Zhou H, Li Y, Liu H, et al. Temporal distribution, influencing factors and pollution sources of urban ambient air quality in Nanchong, China. *Environ. Eng. Res.* 2015;20:260-267.
4. Studer L, Ketabdari M, Marchionni G. Analysis of adaptive traffic control systems design of a decision support system for better choices. *J. Civil Environ. Eng.* 2015;5:195.
5. Solomon S. Segmental assessment of level of traffic congestion on Kality Ring Road to Dukem Bridge [dissertation]. Addis Ababa: Univ. of Addis Ababa; 2015.
6. Sullivan JL, Baker RE, Boyer BA, et al. CO_2 emission benefit of diesel (versus gasoline) powered vehicles. *Environ. Sci. Technol.* 2004;38:3217-3223.
7. Weichenthal S, Ryswyk KV, Kulka R, Sun L, Wallace L, Joseph L. In-vehicle exposures to particulate air pollution in canadian metropolitan areas: The urban transportation exposure study. *Environ. Sci. Technol.* 2014;49:597-605.
8. Chen BP, Ma ZQ. Short-term traffic flow prediction based on ANFIS. In: International Conference on Communication Software and Networks; 27-28 February 2009; Macau, China: IEEE.
9. Zengqiang M, Cunzhi P, Yongqiang W. Road safety evaluation from traffic information based on ANFIS. In: Control Conference, 2008. CCC 2008. 27th Chinese. 2008. IEEE.
10. Soh AC, Rahman RZA, Rhung LG, Sarkan HM. Traffic signal control based on adaptive neural-fuzzy inference system applied to intersection. In: 2011 IEEE Conference on Open Systems (ICOS); 25-28 September 2011; Langkawi, Malaysia: IEEE.
11. Khodayari A, Ghaffari A, Kazemi R, Manavizadeh N. ANFIS based modeling and prediction car following behavior in real traffic flow based on instantaneous reaction delay. In: 2010 13th International IEEE Conference on Intelligent Transportation Systems (ITSC); 19-22 September 2010; Funchal, Portugal: IEEE.
12. Piri J, Kisi O. Modelling solar radiation reached to the Earth using ANFIS, NN-ARX, and empirical models (Case studies: Zahedan and Bojnurd stations). *J. Atmos. Sol-Terr. Phy.* 2015;123:39-47.
13. Younes MK, Nopiah ZM, Basri NE, Basri H, Abushammala MF, Maulud KNA. Solid waste forecasting using modified ANFIS modeling. *J. Air Waste Manage. Assoc.* 2015;65:1229-1238.
14. Karner AA, Eisinger DS, Niemeier DA. Near-roadway air quality: Synthesizing the findings from real-world data. *Environ. Sci. Technol.* 2010;44:5334-5344.
15. Willmott CJ, Matsuura K. Advantages of the mean absolute

- error (MAE) over the root mean square error (RMSE) in assessing average model performance. *Climate Res.* 2005;30:79.
16. Antanasijević DZ, Pocajt VV, Povrenović DS, Ristić MĐ, Perić-Grujić AA. PM₁₀ emission forecasting using artificial neural networks and genetic algorithm input variable optimization. *Sci. Total Environ.* 2013;443:511-519.
 17. Younes MK, Nopiah ZM, Ahmad Basri NE, et al. Landfill area estimation based on integrated waste disposal options and solid waste forecasting using modified ANFIS model. *Waste Manage.* 2016;55:3-11.
 18. Pramanik N, Panda RK. Application of neural network and adaptive neuro-fuzzy inference systems for river flow prediction. *Hydrol. Sci. J.* 2009;54:247-260.
 19. Khatibinia M, Salajegheh J, Fadaee MJ, Salajegheh E. Prediction of failure probability for soil-structure interaction system using modified ANFIS by hybrid of FCM-FPSO. *Asian J. Civil Eng.* 2012;13:1-27.
 20. Lin KP, Pai PF, Lu YM, Chang PT. Revenue forecasting using a least-squares support vector regression model in a fuzzy environment. *Inform. Sci.* 2013;220:196-209.
 21. Shancita I, Masjuki HH, Kalam MA, Rizwanul Fattah IM, Rashed MM, Rashedul HK. A review on idling reduction strategies to improve fuel economy and reduce exhaust emissions of transport vehicles. *Energ. Convers. Manage.* 2014;88:794-807.